



## Safety Data Sheet

Copyright, 2018, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	28-7685-2	<b>Version number:</b>	7.01
<b>Revision date:</b>	22/06/2018	<b>Supersedes date:</b>	04/02/2016
<b>Transportation version number:</b>	1.00 (16/08/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

G182, Ultimate Paste Wax (22-40C): G18211

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Automotive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF  
**Telephone:** +44 (0)870 241 6696  
**E Mail:** info@meguiars.co.uk  
**Website:** www.meguiars.co.uk

#### 1.4. Emergency telephone number

+44 (0)870 241 6696

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Flammable Solid, Category 1 - Flam. Sol. 1; H228

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

##### SIGNAL WORD

DANGER.

**Symbols:**  
GHS02 (Flame) |

**Pictograms**



**HAZARD STATEMENTS:**

H228 Flammable solid.  
H412 Harmful to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS**

**General:**

P102 Keep out of reach of children.

**Prevention:**

P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Response:**

P370 + P378I In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SUPPLEMENTAL INFORMATION**

**Supplemental Hazard Statements:**

EUH066 Repeated exposure may cause skin dryness or cracking.

12% of the mixture consists of components of unknown acute oral toxicity.

Contains 20% of components with unknown hazards to the aquatic environment.

**Notes on labelling**

H304 is not required on the label due to the product's viscosity  
Nota P applied to CAS 64741-65-7.

**2.3. Other hazards**

None known.

**SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Fatty acids, Montan-wax, Ethylene	Mixture			40 - 60	Substance not classified as

**G182, Ultimate Paste Wax (22-40C): G18211**

Esters					hazardous
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics		920-901-0		40 - 60	Asp. Tox. 1, H304; EUH066
Siloxanes and silicones, di-Me	63148-62-9			10 - 30	Substance not classified as hazardous
Starch, hydrogen octenylbutanedioate, aluminium salt	9087-61-0			5 - 10	Substance with a Community level exposure limit in the workplace
Kaolin, calcined	92704-41-1	296-473-8		5 - 10	Substance not classified as hazardous
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8		5 - 10	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; Skin Irrit. 2, H315; STOT SE 3, H336
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc	68988-56-7	273-530-5		1 - 5	Substance not classified as hazardous
Fatty acids, montan-wax	68476-03-9	270-664-6		1 - 5	Substance not classified as hazardous
White mineral oil (petroleum)	8042-47-5	232-455-8		0.1 - 1	Asp. Tox. 1, H304
Naphtha (petroleum), heavy alkylate	64741-65-7	265-067-2		0.1 - 0.5	Asp. Tox. 1, H304 - Nota P Aquatic Chronic 2, H411 Flam. Liq. 3, H226; STOT SE 3, H336; EUH066
Titanium dioxide	13463-67-7	236-675-5		< 0.3	Substance with a Community level exposure limit in the workplace

Note: Any entry in the EC# column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye contact**

Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1 Information on toxicological effects

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools.

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Titanium oxide	13463-67-7	UK HSC	TWA(Inhalable):10 mg/m <sup>3</sup> ;TWA(respirable):4 mg/m <sup>3</sup>	
Aluminium, soluble salts	9087-61-0	UK HSC	TWA:2 mg/m <sup>3</sup>	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:  
Safety glasses with side shields.

##### Applicable Norms/Standards

Use eye protection conforming to EN 166

##### Skin/hand protection

No protective gloves required. Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Nitrile rubber.	No data available	No data available
Polymer laminate	No data available	No data available

*Applicable Norms/Standards*

Use gloves tested to EN 374

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

*Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136: filter types A & P

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Solid.
<b>Specific Physical Form:</b>	Paste
<b>Appearance/Odour</b>	Fruity fragrance; Soft, waxy, cream-coloured paste
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	<i>Not applicable.</i>
<b>Boiling point/boiling range</b>	$\geq 140.6$ °C
<b>Melting point</b>	<i>Not applicable.</i>
<b>Flammability (solid, gas)</b>	Flammable Solid: Category 1. Flammable Solid: Category 1.
<b>Explosive properties</b>	Not classified
<b>Oxidising properties</b>	Not classified
<b>Flash point</b>	$\geq 93.3$ °C [ <i>Test Method:</i> Pensky-Martens Closed Cup]
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Vapour pressure</b>	<i>No data available.</i>
<b>Relative density</b>	0.86 [ <i>Ref Std:</i> WATER=1]
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Vapour density</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity</b>	<i>No data available.</i>
<b>Density</b>	0.86 g/cm <sup>3</sup>

**9.2. Other information**

<b>EU Volatile Organic Compounds</b>	<i>No data available.</i>
<b>Molecular weight</b>	<i>No data available.</i>

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.

Sparks and/or flames.

### 10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.	
-------------	--

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Prolonged or repeated exposure may cause:

Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

#### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

**G182, Ultimate Paste Wax (22-40C): G18211**

the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Inhalation-Vapour		LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Siloxanes and silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Distillates (petroleum), hydrotreated light	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Fatty acids, Montan-wax, Ethylene Esters	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Fatty acids, Montan-wax, Ethylene Esters	Ingestion	Rat	LD50 > 2,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Fatty acids, montan-wax	Dermal		LD50 estimated to be > 5,000 mg/kg
Fatty acids, montan-wax	Ingestion	Rat	LD50 > 15,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Naphtha (petroleum), heavy alkylate	Dermal	Rat	LD50 > 3,000 mg/kg
Naphtha (petroleum), heavy alkylate	Inhalation-Vapour (4 hours)	Rat	LC50 > 9.3 mg/l
Naphtha (petroleum), heavy alkylate	Ingestion	Rat	LD50 > 7,500 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Rabbit	Minimal irritation
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
White mineral oil (petroleum)	Rabbit	No significant irritation
Naphtha (petroleum), heavy alkylate	Rabbit	Minimal irritation
Titanium dioxide	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Rabbit	Mild irritant
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
White mineral oil (petroleum)	Rabbit	Mild irritant
Naphtha (petroleum), heavy alkylate	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

**Skin Sensitisation**

Name	Species	Value
------	---------	-------



**G182, Ultimate Paste Wax (22-40C): G18211**

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Guinea pig	Not classified
Distillates (petroleum), hydrotreated light	Guinea pig	Not classified
White mineral oil (petroleum)	Guinea pig	Not classified
Naphtha (petroleum), heavy alkylate	Guinea pig	Not classified
Titanium dioxide	Human and animal	Not classified

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	In vivo	Not mutagenic
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
Naphtha (petroleum), heavy alkylate	In Vitro	Not mutagenic
Naphtha (petroleum), heavy alkylate	In vivo	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not available	Not carcinogenic
Distillates (petroleum), hydrotreated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Naphtha (petroleum), heavy alkylate	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

**Reproductive Toxicity**
**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for female reproduction	Not available	NOAEL NA	1 generation
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for male reproduction	Not available	NOAEL NA	28 days
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for development	Not available	NOAEL NA	during gestation
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350	during gestation

**G182, Ultimate Paste Wax (22-40C): G18211**

				mg/kg/day	
Naphtha (petroleum), heavy alkylate	Inhalation	Not classified for development	Rat	NOAEL 900 ppm	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), hydrotreated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), hydrotreated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Naphtha (petroleum), heavy alkylate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Not available	NOAEL Not available	
Naphtha (petroleum), heavy alkylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	
Naphtha (petroleum), heavy alkylate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Not available	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver   immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Naphtha (petroleum), heavy alkylate	Dermal	bone marrow	Not classified	Rat	NOAEL 2,000 mg/kg/day	4 weeks
Naphtha (petroleum), heavy alkylate	Dermal	hematopoietic system	Not classified	Rat	NOAEL 2,000 mg/kg	4 weeks
Naphtha (petroleum), heavy alkylate	Inhalation	hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 10.2 mg/l	13 weeks
Naphtha (petroleum), heavy alkylate	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	4 weeks
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

Name	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Aspiration hazard
Distillates (petroleum), hydrotreated light	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard
Naphtha (petroleum), heavy alkylate	Aspiration hazard

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

## SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Fatty acids, Montan-wax, Ethylene Esters	Mixture		Data not available or insufficient for classification			
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Rainbow trout	Estimated	96 hours	Lethal Level 50%	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Water flea	Estimated	48 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Green Algae	Estimated	72 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Green Algae	Estimated	72 hours	No obs Effect Level	1,000 mg/l
Siloxanes and silicones, di-Me	63148-62-9		Data not available or insufficient for classification			
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	EC50	1 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Rainbow trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l
Kaolin, calcined	92704-41-1	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	EC50	2,500 mg/l
Kaolin, calcined	92704-41-1	Water flea	Estimated	48 hours	EC50	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	Effect Concentration 10%	41 mg/l
Kaolin, calcined	92704-41-1	Rainbow trout	Estimated	30 days	NOEC	>100 mg/l
Starch, hydrogen octenylbutanedioate, aluminium salt	9087-61-0		Data not available or insufficient for classification			
Fatty acids, montan-wax	68476-03-9	Zebra Fish	Experimental	96 hours	LC50	>500 mg/l
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc	68988-56-7		Data not available or insufficient for classification			
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l

**G182, Ultimate Paste Wax (22-40C): G18211**

White mineral oil (petroleum)	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l
Naphtha (petroleum), heavy alkylate	64741-65-7		Data not available or insufficient for classification			
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Fatty acids, Montan-wax, Ethylene Esters	Mixture	Data not availbl-insufficient			N/A	
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Estimated Biodegradation	28 days	BOD	31.3 % BOD/ThBOD	OECD 301F - Manometric respirometry
Siloxanes and silicones, di-Me	63148-62-9	Data not availbl-insufficient			N/A	
Distillates (petroleum), hydrotreated light	64742-47-8	Data not availbl-insufficient			N/A	
Kaolin, calcined	92704-41-1	Data not availbl-insufficient			N/A	
Starch, hydrogen octenylbutanedioate, aluminium salt	9087-61-0	Data not availbl-insufficient			N/A	
Fatty acids, montan-wax	68476-03-9	Data not availbl-insufficient			N/A	
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc	68988-56-7	Data not availbl-insufficient			N/A	
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Naphtha (petroleum), heavy alkylate	64741-65-7	Estimated Photolysis		Photolytic half-life (in air)	<4.01 days (t 1/2)	Other methods
Naphtha (petroleum), heavy alkylate	64741-65-7	Experimental Biodegradation	28 days	BOD	8-22 % weight	OECD 301D - Closed bottle test
Titanium dioxide	13463-67-7	Data not availbl-insufficient			N/A	

**12.3 : Bioaccumulative potential**

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Fatty acids, Montan-wax, Ethylene Esters	Mixture	Estimated Bioconcentration		Bioaccumulation factor	20.5	Other methods
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Starch, hydrogen	9087-61-0	Data not available	N/A	N/A	N/A	N/A

**G182, Ultimate Paste Wax (22-40C): G18211**

octenylbutanedioate, aluminium salt		or insufficient for classification				
Fatty acids, montan-wax	68476-03-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc	68988-56-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha (petroleum), heavy alkylate	64741-65-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulation factor	9.6	Other methods

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

**EU waste code (product as sold)**

20 01 13\* Solvents

**SECTION 14: Transportation information**

ADR: UN1325 Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4,1; II; (E); F1

IATA: UN1325 Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4,1; II

IMDG: UN1325 Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4,1; II; FA, SG

**SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### Global inventory status

Contact manufacturer for more information The components of this product are in compliance with the chemical notification requirements of TSCA.

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

## SECTION 16: Other information

#### List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Revision information:

CLP: Ingredient table information was deleted.  
Label: CLP Classification information was modified.  
Label: CLP Environmental Hazard Statements information was added.  
Label: CLP Percent Unknown information was modified.  
Label: CLP Precautionary - Prevention information was modified.  
Label: CLP Precautionary - Response information was modified.  
Label: CLP Supplemental Hazard Statements information was added.  
Label: Graphic information was modified.  
Section 3: Composition/ Information of ingredients table information was added.  
Section 3: Composition/ Information of ingredients table information was deleted.  
Section 4: First aid for eye contact information information was modified.  
Section 4: First aid for skin contact information information was modified.  
Section 5: Fire - Advice for fire fighters information information was modified.  
Section 6: Accidental release personal information information was modified.  
Section 7: Conditions safe storage information was modified.  
Section 7: Precautions safe handling information information was modified.  
Section 8: glove data value information was modified.  
Section 8: Occupational exposure limit table information was modified.  
Section 8: Personal Protection - Skin/hand information information was modified.  
Section 9: Flash point information information was modified.  
Section 9: Property description for optional properties information was modified.  
Section 11: Acute Toxicity table information was modified.  
Section 11: Aspiration Hazard Table information was modified.  
Section 11: Cancer Hazards information information was added.

Section 11: Carcinogenicity Table information was modified.  
Section 11: Germ Cell Mutagenicity Table information was modified.  
Section 11: Health Effects - Skin information information was modified.  
Section 11: Reproductive Toxicity Table information was modified.  
Section 11: Serious Eye Damage/Irritation Table information was modified.  
Section 11: Single exposure may cause standard phrases information was deleted.  
Section 11: Skin Corrosion/Irritation Table information was modified.  
Section 11: Skin Sensitization Table information was modified.  
Section 11: Target Organs - Repeated Table information was modified.  
Section 11: Target Organs - Single Table information was modified.  
Section 12: Component ecotoxicity information information was modified.  
Section 12: No PBT/vPvB information available warning information was modified.  
Section 12: Persistence and Degradability information information was modified.  
Section 12: Biocumulative potential information information was modified.  
Section 13: Standard Phrase Category Waste GHS information was modified.  
Section 14: Transportation classification information was modified.  
Section 15: Carcinogenicity information information was added.  
Section 15: Chemical Safety Assessment information was modified.  
Section 15: Label remarks and EU Detergent information was modified.  
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material.  
information was modified.  
Section 16: Web address information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**Meguiar's, Inc. United Kingdom SDSs are available at [www.meguiars.co.uk](http://www.meguiars.co.uk)**