



## Safety Data Sheet

Copyright, 2019, Meguiar's Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	27-5146-9	<b>Version number:</b>	8.01
<b>Revision date:</b>	16/12/2019	<b>Supersedes date:</b>	05/11/2019
<b>Transportation version number:</b>	1.00 (29/09/2010)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

G70, Gold Class Paste Car Wax (21-124A): G7014

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Automotive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF  
**Telephone:** +44 (0)870 241 6696  
**E Mail:** info@meguiars.co.uk  
**Website:** www.meguiars.co.uk

#### 1.4. Emergency telephone number

+44 (0)870 241 6696

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Flammable Solid, Category 1 - Flam. Sol. 1; H228

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

##### SIGNAL WORD

DANGER.

**Symbols:**

GHS02 (Flame) |

**Pictograms****HAZARD STATEMENTS:**

H228 Flammable solid.

**PRECAUTIONARY STATEMENTS****General:**

P102 Keep out of reach of children.

**Prevention:**

P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Response:**

P370 + P378I In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**SUPPLEMENTAL INFORMATION:****Supplemental Hazard Statements:**

EUH066 Repeated exposure may cause skin dryness or cracking.

13% of the mixture consists of components of unknown acute oral toxicity.

Contains 13% of components with unknown hazards to the aquatic environment.

**Notes on labelling**

H304 is not required on the label due to the product's viscosity

Nota P applied to CASRN 8052-41-3. H228 assigned based on test data indicating that this product is a flammable solid.

**2.3. Other hazards**

None known.

**SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics		920-901-0		30 - 50	Asp. Tox. 1, H304; EUH066
Polymer Protectant	Trade Secret			10 - 30	Substance with a Community level exposure limit in the workplace
Kaolin, calcined	92704-41-1	296-473-8		5 - 15	Substance not classified as hazardous
Silicone resin	Trade			5 - 15	Substance not classified as

	Secret				hazardous
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics		927-676-8		1 - 10	Asp. Tox. 1, H304; EUH066
Fatty acids, montan-wax	68476-03-9	270-664-6		1 - 5	Substance not classified as hazardous
Glycerol poly(oxyethylene, oxypropylene) ether	9082-00-2			1 - 5	Substance not classified as hazardous
Rheology Additive	Trade Secret			0.5 - 1.5	Substance not classified as hazardous
stoddard solvent	8052-41-3	232-489-3		0.1 - 0.5	Asp. Tox. 1, H304; STOT RE 1, H372 - Nota P Skin Irrit. 2, H315; Aquatic Chronic 3, H412
Anatase TiO2	1317-70-0	215-280-1		< 0.25	Substance with a Community level exposure limit in the workplace

Note: Any entry in the EC# column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.  
Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye contact

No need for first aid is anticipated.

#### If swallowed

Rinse mouth. If you are concerned, get medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

#### Condition

Aldehydes.  
formaldehyde  
Carbon monoxide  
Carbon dioxide.  
Irritant vapours or gases.  
Oxides of nitrogen.

During combustion.  
During combustion.  
During combustion.  
During combustion.  
During combustion.  
During combustion.

### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
Titanium oxide	1317-70-0	UK HSC	TWA(Inhalable):10 mg/m <sup>3</sup> ;TWA(respirable):4 mg/m <sup>3</sup>	
Polymer Protectant	Trade Secret	UK HSC	TWA:2 mg/m <sup>3</sup>	

UK HSC : UK Health and Safety Commission  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

**Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

**Recommended monitoring procedures:**Information on recommended monitoring procedures can be obtained from UK HSC

**8.2. Exposure controls****8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

None required.

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

<b>Material</b>	<b>Thickness (mm)</b>	<b>Breakthrough Time</b>
Polymer laminate	No data available	No data available

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used:Nitrile rubber.

*Applicable Norms/Standards*

Use gloves tested to EN 374

**Respiratory protection**

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

*Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136: filter types A & P

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Appearance**

**Physical state**

Solid.

**Colour**

Dull Yellow, Soft White

**Specific Physical Form:**

Paste

**Odor**

Pleasant Odor

**Odour threshold**

*No data available.*

**pH**

*Not applicable.*

**Boiling point/boiling range**

185 °C

**Melting point**

*Not applicable.*

**Flammability (solid, gas)**

Flammable Solid: Category 1.

**Explosive properties**

Not classified

**Oxidising properties**

Not classified

**Flash point**

>= 93.3 °C [*Test Method*:Pensky-Martens Closed Cup]

**Autoignition temperature**

*No data available.*

**Flammable Limits(LEL)**

*No data available.*

**Flammable Limits(UEL)**

*No data available.*

**Vapour pressure**

*No data available.*

**Relative density**

0.85 [*Ref Std*:WATER=1]

**Water solubility**

Nil

**Solubility- non-water**

*No data available.*

**Partition coefficient: n-octanol/water**

*No data available.*

**Evaporation rate**

*No data available.*

**Vapour density**

*No data available.*

**Decomposition temperature**

*No data available.*

**Viscosity**

*No data available.*

**Density**

0.85 g/cm<sup>3</sup>

### 9.2. Other information

**EU Volatile Organic Compounds**

*No data available.*

**Molecular weight**

*No data available.*

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.

Sparks and/or flames.

#### 10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

#### 10.6 Hazardous decomposition products

##### Substance

##### Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation

May be harmful if inhaled. May cause additional health effects (see below).

##### Skin contact

Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

##### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

##### Ingestion

No known health effects.

#### Additional Health Effects:

##### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE <sub>20</sub> - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Inhalation-Vapour		LC50 estimated to be 20 - 50 mg/l

**G70, Gold Class Paste Car Wax (21-124A): G7014**

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Silicone resin	Dermal	Rabbit	LD50 > 19,400 mg/kg
Silicone resin	Ingestion	Rat	LD50 > 17,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Inhalation-Vapour		LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Inhalation-Vapour	Professional judgement	LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Fatty acids, montan-wax	Dermal		LD50 estimated to be > 5,000 mg/kg
Fatty acids, montan-wax	Ingestion	Rat	LD50 > 15,000 mg/kg
Glycerol poly(oxyethylene, oxypropylene) ether	Dermal	Rabbit	LD50 > 5,000 mg/kg
Glycerol poly(oxyethylene, oxypropylene) ether	Ingestion	Rat	LD50 > 10,000 mg/kg
Rheology Additive	Dermal		LD50 estimated to be > 5,000 mg/kg
Rheology Additive	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 12.6 mg/l
Rheology Additive	Ingestion	Rat	LD50 > 5,000 mg/kg
stoddard solvent	Inhalation-Vapour		LC50 estimated to be 20 - 50 mg/l
stoddard solvent	Dermal	Rabbit	LD50 > 3,000 mg/kg
stoddard solvent	Ingestion	Rat	LD50 > 5,000 mg/kg
Anatase TiO2	Dermal	Rabbit	LD50 > 10,000 mg/kg
Anatase TiO2	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Anatase TiO2	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Rabbit	Minimal irritation
Silicone resin	Rabbit	No significant irritation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Rabbit	Minimal irritation
Rheology Additive	Rat	No significant irritation
stoddard solvent	Rabbit	Irritant
Anatase TiO2	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Rabbit	Mild irritant
Silicone resin	Rabbit	No significant irritation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Rabbit	Mild irritant
Rheology Additive	Rabbit	No significant irritation
stoddard solvent	Rabbit	No significant irritation
Anatase TiO2	Rabbit	No significant irritation

**Skin Sensitisation**

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Guinea pig	Not classified
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Guinea pig	Not classified



stoddard solvent	Guinea pig	Not classified
Anatase TiO2	Human and animal	Not classified

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	In vivo	Not mutagenic
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	In vivo	Not mutagenic
stoddard solvent	In vivo	Not mutagenic
stoddard solvent	In Vitro	Some positive data exist, but the data are not sufficient for classification
Anatase TiO2	In Vitro	Not mutagenic
Anatase TiO2	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not available	Not carcinogenic
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not available	Not carcinogenic
stoddard solvent	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
stoddard solvent	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Anatase TiO2	Ingestion	Multiple animal species	Not carcinogenic
Anatase TiO2	Inhalation	Rat	Carcinogenic.

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for female reproduction	Not available	NOAEL NA	1 generation
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for male reproduction	Not available	NOAEL NA	28 days
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for development	Not available	NOAEL NA	during gestation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Not available	NOAEL NA	1 generation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Not available	NOAEL NA	28 days
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	28 days
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Not available	NOAEL NA	during gestation
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	during gestation
stoddard solvent	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
stoddard solvent	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
stoddard solvent	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
stoddard solvent	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
stoddard solvent	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
stoddard solvent	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
stoddard solvent	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
stoddard solvent	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
stoddard solvent	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
stoddard solvent	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Anatase TiO <sub>2</sub>	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Anatase TiO <sub>2</sub>	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

Name	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Aspiration hazard
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Aspiration hazard
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	Aspiration hazard
stoddard solvent	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result

**G70, Gold Class Paste Car Wax (21-124A): G7014**

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Water flea	Estimated	48 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Green Algae	Estimated	72 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Rainbow trout	Estimated	96 hours	Lethal Level 50%	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Green Algae	Estimated	72 hours	No obs Effect Level	1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Water flea	Experimental	21 days	No obs Effect Level	1 mg/l
Polymer Protectant	Trade Secret		Data not available or insufficient for classification			
Kaolin, calcined	92704-41-1	Water flea	Estimated	48 hours	EC50	>100 mg/l
Kaolin, calcined	92704-41-1	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	EC50	2,500 mg/l
Kaolin, calcined	92704-41-1	Rainbow trout	Estimated	30 days	NOEC	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	Effect Concentration 10%	41 mg/l
Silicone resin	Trade Secret		Data not available or insufficient for classification			
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Green Algae	Estimated	72 hours	No obs Effect Level	1,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Green Algae	Estimated	72 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Water flea	Experimental	48 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Rainbow trout	Experimental	96 hours	Lethal Level 50%	>88,444 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Water flea	Estimated	48 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Rainbow trout	Estimated	96 hours	Lethal Level 50%	>1,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Crustacea other	Estimated	96 hours	Lethal Level 50%	>10,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Green Algae	Estimated	72 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Green Algae	Estimated	72 hours	No obs Effect Level	1,000 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Water flea	Experimental	21 days	No obs Effect Level	1 mg/l
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Water flea	Experimental	21 days	No obs Effect Level	1 mg/l
Glycerol poly(oxyethylene, oxypropylene) ether	9082-00-2	Inland Silverside	Estimated	96 hours	LC50	650 mg/l

**G70, Gold Class Paste Car Wax (21-124A): G7014**

Fatty acids, montan-wax	68476-03-9	Zebra Fish	Experimental	96 hours	LC50	>500 mg/l
Rheology Additive	Trade Secret	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Rheology Additive	Trade Secret	Water flea	Estimated	48 hours	EC50	>100 mg/l
Rheology Additive	Trade Secret	Green algae	Estimated	72 hours	EC50	>100 mg/l
stoddard solvent	8052-41-3	Green Algae	Estimated	96 hours	Effect Level 50%	2.5 mg/l
stoddard solvent	8052-41-3	Crustacea	Estimated	96 hours	LC50	3.5 mg/l
stoddard solvent	8052-41-3	Rainbow trout	Estimated	96 hours	Lethal Level 50%	41.4 mg/l
stoddard solvent	8052-41-3	Water flea	Estimated	21 days	NOEC	0.28 mg/l
stoddard solvent	8052-41-3	Green Algae	Estimated	96 hours	No obs Effect Level	0.76 mg/l
Anatase TiO2	1317-70-0		Data not available or insufficient for classification			

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Estimated Biodegradation	28 days	BOD	31.3 % BOD/ThBOD	OECD 301F - Manometric respirometry
Polymer Protectant	Trade Secret	Data not available or insufficient			N/A	
Kaolin, calcined	92704-41-1	Data not available or insufficient			N/A	
Silicone resin	Trade Secret	Data not available or insufficient			N/A	
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Estimated Biodegradation	28 days	BOD	31.3 % BOD/ThBOD	OECD 301F - Manometric respirometry
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Experimental Biodegradation	28 days	BOD	22 % BOD/ThBOD	OECD 301F - Manometric respirometry
Glycerol poly(oxyethylene, oxypropylene) ether	9082-00-2	Data not available or insufficient			N/A	
Fatty acids, montan-wax	68476-03-9	Data not available or insufficient			N/A	
Rheology Additive	Trade Secret	Estimated Biodegradation	28 days	BOD	3 % BOD/ThBOD	OECD 301D - Closed bottle test
stoddard solvent	8052-41-3	Experimental Photolysis		Photolytic half-life (in air)	6.49 days (t 1/2)	Other methods
stoddard solvent	8052-41-3	Experimental Biodegradation	28 days	CO2 evolution	>63 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Anatase TiO2	1317-70-0	Data not available or insufficient			N/A	

**12.3 : Bioaccumulative potential**

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polymer Protectant	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**G70, Gold Class Paste Car Wax (21-124A): G7014**

Silicone resin	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	927-676-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerol poly(oxyethylene, oxypropylene) ether	9082-00-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fatty acids, montan-wax	68476-03-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Rheology Additive	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
stoddard solvent	8052-41-3	Estimated Bioconcentration		Log Kow	6.4	Other methods
Anatase TiO2	1317-70-0	Estimated BCF-Carp	42 days	Bioaccumulation factor	<10	Other methods

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

**EU waste code (product as sold)**

20 01 13\* Solvents

**SECTION 14: Transportation information**

IATA: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II.

ADR: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; (E); F1.

IMDG: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; EMS: FA, SG.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Anatase TiO <sub>2</sub>	1317-70-0	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

## SECTION 16: Other information

### List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

### Revision information:

Section 3: Composition/ Information of ingredients table information was modified.  
Section 5: Hazardous combustion products table information was modified.  
Section 11: Acute Toxicity table information was modified.  
Section 11: Aspiration Hazard Table information was modified.  
Section 11: Carcinogenicity Table information was modified.  
Section 11: Germ Cell Mutagenicity Table information was modified.  
Section 11: Reproductive Toxicity Table information was modified.  
Section 11: Serious Eye Damage/Irritation Table information was modified.  
Section 11: Skin Corrosion/Irritation Table information was modified.  
Section 11: Skin Sensitization Table information was modified.  
Section 11: Target Organs - Repeated Table information was modified.  
Section 11: Target Organs - Single Table information was modified.  
Section 12: Component ecotoxicity information information was modified.  
Section 12: Persistence and Degradability information information was modified.  
Section 12: Bioaccumulative potential information information was modified.  
Section 14: Transportation classification information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union,

you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**Meguiar's, Inc. United Kingdom SDSs are available at [www.meguiars.co.uk](http://www.meguiars.co.uk)**