



## Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	28-7343-8	<b>Version number:</b>	5.00
<b>Revision date:</b>	23/10/2017	<b>Supersedes date:</b>	19/06/2017
<b>Transportation version number:</b>	1.00 (03/06/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

M101, Foam Cut Compound (21-89B): M10132

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Automotive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF  
**Telephone:** +44 (0)870 241 6696  
**E Mail:** info@meguiars.co.uk  
**Website:** www.meguiars.co.uk

#### 1.4. Emergency telephone number

+44 (0)870 241 6696

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336  
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

WARNING.

**Symbols:**

GHS07 (Exclamation mark) |GHS09 (Environment) |

**Pictograms**



**Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
Naphthol Spirits (C10-C12)	64742-48-9	265-150-3	7 - 14
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8	5 - 10
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	265-198-5	1 - 5

**HAZARD STATEMENTS:**

H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS**

**General:**

P102 Keep out of reach of children.

**Prevention:**

P261A Avoid breathing vapours.  
P273 Avoid release to the environment.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.

**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SUPPLEMENTAL INFORMATION**

**Supplemental Hazard Statements:**

EUH208 Contains Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

11% of the mixture consists of components of unknown acute inhalation toxicity.

**Information required per Regulation (EU) No 528/2012 on Biocidal Products:**

Contains a biocidal product: Contains C(M)IT/MIT (3:1). May produce an allergic reaction.

**Notes on labelling**

H304 is not required on the label due to the product's viscosity

**M101, Foam Cut Compound (21-89B): M10132**

Nota P applied to CAS 64742-48-9

**2.3. Other hazards**

None known.

**SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Non-Hazardous Ingredients	Mixture			30 - 60	Substance not classified as hazardous
Aluminium Oxide (non-fibrous)	1344-28-1	215-691-6		10 - 30	Substance with a Community level exposure limit in the workplace
Naphthol Spirits (C10-C12)	64742-48-9	265-150-3		7 - 14	Asp. Tox. 1, H304 - Nota P Aquatic Chronic 2, H411 Flam. Liq. 3, H226; STOT SE 3, H336; EUH066
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8		5 - 10	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; Skin Irrit. 2, H315; STOT SE 3, H336
conditioners	Trade Secret			< 5	Substance not classified as hazardous
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	265-198-5		1 - 5	Asp. Tox. 1, H304 Flam. Liq. 3, H226; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1
White mineral oil (petroleum)	8042-47-5	232-455-8		1 - 5	Asp. Tox. 1, H304
Glycerin	56-81-5	200-289-5		1 - 5	Substance with a Community level exposure limit in the workplace
Sorbitan monooleate, ethoxylated	9005-65-6	500-019-9		1 - 5	Substance not classified as hazardous
Triethanolamine	102-71-6	203-049-8		0.5 - 1.5	Substance not classified as hazardous
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9			<= 0.0015	Acute Tox. 3, H331; Acute Tox. 3, H311; Acute Tox. 3, H301; Skin Corr. 1B, H314; Skin Sens. 1A, H317; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

##### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

##### Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

##### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

##### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons.	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

#### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from acids. Store away from strong bases. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
Aluminium Oxide (non-fibrous)	1344-28-1	UK HSC	TWA(as inhalable dust):10 mg/m <sup>3</sup> ;TWA(as respirable dust):4 mg/m <sup>3</sup>	
Glycerin	56-81-5	UK HSC	TWA(as mist):10 mg/m <sup>3</sup>	
Naphthol Spirits (C10-C12)	64742-48-9	Manufacturer determined	TWA:100 ppm	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

**Eye/face protection**

None required.

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

<b>Material</b>	<b>Thickness (mm)</b>	<b>Breakthrough Time</b>
Nitrile rubber.	No data available	No data available

*Applicable Norms/Standards*

Use gloves tested to EN 374

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

*Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136: filter types A & P

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Appearance/Odour</b>	Sweet odour; White, creamy lotion
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	8.4 - 8.9
<b>Boiling point/boiling range</b>	$\geq 100$ °C
<b>Melting point</b>	<i>Not applicable.</i>
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Explosive properties</b>	Not classified
<b>Oxidising properties</b>	Not classified
<b>Flash point</b>	$\geq 93.3$ °C [Test Method: Closed Cup]
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Vapour pressure</b>	<i>No data available.</i>
<b>Relative density</b>	1.18 [Ref Std: WATER=1]
<b>Water solubility</b>	Moderate
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Vapour density</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity</b>	24,000 - 38,000 mPa-s
<b>Density</b>	1.18 g/cm <sup>3</sup>

## 9.2. Other information

EU Volatile Organic Compounds

*No data available.*

Molecular weight

*No data available.*

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Temperatures above the boiling point.

### 10.5 Incompatible materials

Strong acids.

Strong bases.

Strong oxidising agents.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

#### Eye contact

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**M101, Foam Cut Compound (21-89B): M10132****Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminium Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium Oxide (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Naphthol Spirits (C10-C12)	Inhalation-Vapour (4 hours)		LC50 estimated to be 20 - 50 mg/l
Naphthol Spirits (C10-C12)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Naphthol Spirits (C10-C12)	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Distillates (petroleum), hydrotreated light	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Sorbitan monooleate, ethoxylated	Dermal		LD50 estimated to be > 5,000 mg/kg
Sorbitan monooleate, ethoxylated	Ingestion	Rat	LD50 > 38,000 mg/kg
Solvent naphtha (petroleum), heavy aromatic	Dermal	Rabbit	LD50 > 2,000 mg/kg
Solvent naphtha (petroleum), heavy aromatic	Ingestion	Rat	LD50 > 5,000 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
conditioners	Dermal		LD50 estimated to be > 5,000
conditioners	Ingestion		LD50 estimated to be > 5,000
Triethanolamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
Triethanolamine	Ingestion	Rat	LD50 9,000 mg/kg
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Dermal	Rabbit	LD50 87 mg/kg
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value



**M101, Foam Cut Compound (21-89B): M10132**

Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
Naphthol Spirits (C10-C12)	Rabbit	Mild irritant
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
White mineral oil (petroleum)	Rabbit	No significant irritation
Solvent naphtha (petroleum), heavy aromatic	Rabbit	Irritant
Glycerin	Rabbit	No significant irritation
conditioners	Human	Minimal irritation
Triethanolamine	Rabbit	Minimal irritation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Rabbit	Corrosive

**Serious Eye Damage/Irritation**

Name	Species	Value
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
Naphthol Spirits (C10-C12)	Rabbit	Mild irritant
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
White mineral oil (petroleum)	Rabbit	Mild irritant
Solvent naphtha (petroleum), heavy aromatic	Rabbit	Mild irritant
Glycerin	Rabbit	No significant irritation
conditioners	Rabbit	Mild irritant
Triethanolamine	Rabbit	Mild irritant
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Rabbit	Corrosive

**Skin Sensitisation**

Name	Species	Value
Naphthol Spirits (C10-C12)	Guinea pig	Not classified
Distillates (petroleum), hydrotreated light	Guinea pig	Not classified
White mineral oil (petroleum)	Guinea pig	Not classified
Solvent naphtha (petroleum), heavy aromatic	Guinea pig	Not classified
Glycerin	Guinea pig	Not classified
conditioners	Human	Not classified
Triethanolamine	Human	Not classified
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Human and animal	Sensitising

**Photosensitisation**

Name	Species	Value
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Human and animal	Not sensitising

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Aluminium Oxide (non-fibrous)	In Vitro	Not mutagenic
Naphthol Spirits (C10-C12)	In Vitro	Not mutagenic
Naphthol Spirits (C10-C12)	In vivo	Not mutagenic
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
conditioners	In Vitro	Not mutagenic

**M101, Foam Cut Compound (21-89B): M10132**

conditioners	In vivo	Not mutagenic
Triethanolamine	In Vitro	Not mutagenic
Triethanolamine	In vivo	Not mutagenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	In vivo	Not mutagenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Aluminium Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Naphthol Spirits (C10-C12)	Not specified.	Not available	Not carcinogenic
Distillates (petroleum), hydrotreated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Solvent naphtha (petroleum), heavy aromatic	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Triethanolamine	Dermal	Multiple animal species	Not carcinogenic
Triethanolamine	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Dermal	Mouse	Not carcinogenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Rat	Not carcinogenic

**Reproductive Toxicity**
**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Naphthol Spirits (C10-C12)	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	prematemg & during gestation
Naphthol Spirits (C10-C12)	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	28 days
Naphthol Spirits (C10-C12)	Not specified.	Not classified for development	Rat	NOAEL Not available	during gestation
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
Triethanolamine	Ingestion	Not classified for development	Mouse	NOAEL 1,125 mg/kg/day	during organogenesis

**M101, Foam Cut Compound (21-89B): M10132**

Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

**Target Organ(s)**
**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Naphthol Spirits (C10-C12)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphthol Spirits (C10-C12)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), hydrotreated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Solvent naphtha (petroleum), heavy aromatic	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Solvent naphtha (petroleum), heavy aromatic	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL Not available	
Solvent naphtha (petroleum), heavy aromatic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminium Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium Oxide (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver   immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Glycerin	Inhalation	respiratory system   heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system   hematopoietic	Not classified	Rat	NOAEL 10,000	2 years

**M101, Foam Cut Compound (21-89B): M10132**

		system   liver   kidney and/or bladder			mg/kg/day	
conditioners	Ingestion	heart   hematopoietic system   liver	Not classified	Rat	NOAEL 4,800 mg/kg/day	13 weeks
conditioners	Ingestion	kidney and/or bladder	Not classified	Mouse	NOAEL 13,000 mg/kg/day	13 weeks
Triethanolamine	Dermal	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,000 mg/kg/day	2 years
Triethanolamine	Dermal	liver	Not classified	Mouse	NOAEL 4,000 mg/kg/day	13 weeks
Triethanolamine	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,000 mg/kg/day	2 years
Triethanolamine	Ingestion	liver	Not classified	Guinea pig	NOAEL 1,600 mg/kg/day	24 weeks

**Aspiration Hazard**

Name	Value
Naphthol Spirits (C10-C12)	Aspiration hazard
Distillates (petroleum), hydrotreated light	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard
Solvent naphtha (petroleum), heavy aromatic	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1		Experimental	96 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Naphthol Spirits (C10-C12)	64742-48-9	Water flea	Unknown	21 days	NOEC	<1 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Rainbow trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	EC50	1 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l

**M101, Foam Cut Compound (21-89B): M10132**

Distillates (petroleum), hydrotreated light conditioners	64742-47-8 Trade Secret	Water flea Zebra Fish	Estimated	21 days 96 hours	No obs Effect Level LC50	0.48 mg/l >100 mg/l
Glycerin	56-81-5	Rainbow trout	Experimental	96 hours	LC50	54,000 mg/l
Glycerin	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	Water flea	Experimental	48 hours	EC50	0.95 mg/l
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	Rainbow trout	Experimental	96 hours	LC50	2.34 mg/l
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	Green Algae	Experimental	96 hours	IC50	4.2 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Copepods	Estimated	48 hours	Lethal Level 50%	>10,000 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Green Algae	Estimated	72 hours	Effect Level 50%	58.84 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Green Algae	Estimated	72 hours	Effect Concentration 10%	19.05 mg/l
Sorbitan monooleate, ethoxylated	9005-65-6	Water flea	Estimated	21 days	No obs Effect Level	10 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l
Triethanolamine	102-71-6	Fathead minnow	Experimental	96 hours	LC50	11,800 mg/l
Triethanolamine	102-71-6	Water flea	Experimental	48 hours	EC50	609.98 mg/l
Triethanolamine	102-71-6	Green algae	Experimental	72 hours	EC50	512 mg/l
Triethanolamine	102-71-6	Green Algae	Experimental	72 hours	Effect Concentration 10%	26 mg/l
Triethanolamine	102-71-6	Water flea	Experimental	21 days	NOEC	16 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Diatom	Experimental	72 hours	EC50	0.021 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Water flea	Experimental	48 hours	EC50	0.18 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Diatom	Experimental	72 hours	NOEC	0.01 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminium Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphthol Spirits (C10-C12)	64742-48-9	Unknown Biodegradation	28 days	Percent degraded	31.3 % weight	Other methods

**M101, Foam Cut Compound (21-89B): M10132**

Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
conditioners	Trade Secret	Estimated Biodegradation	28 days	BOD	64 % weight	OECD 301D - Closed bottle test
Glycerin	56-81-5	Experimental Biodegradation	14 days	BOD	63 % BOD/ThBOD	OECD 301C - MITI test (I)
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	Experimental Biodegradation	28 days	BOD	39 % weight	OECD 301D - Closed bottle test
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	Estimated Photolysis		Photolytic half-life (in air)	2.1 days (t 1/2)	Other methods
Sorbitan monooleate, ethoxylated	9005-65-6	Experimental Biodegradation	28 days	CO2 evolution	61 % weight	Other methods
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Triethanolamine	102-71-6	Experimental Biodegradation	19 days	Dissolv. Organic Carbon Deplet	96 % weight	Other methods
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.3 : Bioaccumulative potential**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminium Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphthol Spirits (C10-C12)	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
conditioners	Trade Secret	Estimated Bioconcentration		Bioaccumulation factor	7.4	Estimated: Bioconcentration factor
Glycerin	56-81-5	Experimental Bioconcentration		Log Kow	-1.76	Other methods
Solvent naphtha (petroleum), heavy aromatic	64742-94-5	Experimental Bioconcentration		Log Kow	6.1	Other methods
Sorbitan monooleate, ethoxylated	9005-65-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Triethanolamine	102-71-6	Experimental BCF-Carp	42 days	Bioaccumulation factor	<3.9	Other methods
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5. Results of the PBT and vPvB assessment**

No information available at this time, contact manufacturer for more details

**12.6. Other adverse effects**

No information available.

**M101, Foam Cut Compound (21-89B): M10132**

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

### EU waste code (product as sold)

120109\* Machining emulsions and solutions free of halogens

## SECTION 14: Transportation information

ADR: UN3082 Environmentally Hazardous Substance, Liquid, N.O.S. (Solvent naphtha (petroleum), heavy aromatic); 9; III; (E); M6

IMDG: UN3082; Environmentally Hazardous Substance, Liquid, N.O.S (Solvent naphtha (petroleum), heavy aromatic); 9; III; Marine Pollutant: Solvent naphtha (petroleum), heavy aromatic

IATA: UN3082; Environmentally Hazardous Substance, Liquid, N.O.S. (Solvent naphtha (petroleum), heavy aromatic); 9; III.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Triethanolamine	102-71-6	Gr. 3: Not classifiable	International Agency for Research on Cancer

#### Global inventory status

Contact manufacturer for more information The components of this product are in compliance with the chemical notification requirements of TSCA.

### 15.2. Chemical Safety Assessment

Not applicable

## SECTION 16: Other information

### List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

**Revision information:**

Label: CLP Classification information was modified.  
Label: CLP Percent Unknown information was deleted.  
Label: CLP Percent Unknown information was modified.  
Label: CLP Precautionary - General information was modified.  
Label: CLP Precautionary - Prevention information was modified.  
Label: CLP Precautionary - Response information was added.  
Section 3: Composition/ Information of ingredients table information was modified.  
Section 5: Fire - Advice for fire fighters information information was modified.  
Section 9: Property description for optional properties information was modified.  
Section 12: Component ecotoxicity information information was modified.  
Prints No Data if Adverse effects information is not present information was added.  
Section 12: Persistence and Degradability information information was modified.  
Section 12: Biocumulative potential information information was modified.  
Section 13: Standard Phrase Category Waste GHS information was modified.  
Section 14: Transportation classification information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**Meguiar's, Inc. United Kingdom MSDSs are available at [www.meguiars.co.uk](http://www.meguiars.co.uk)**