



## Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	36-4891-2	<b>Version number:</b>	1.01
<b>Revision date:</b>	24/01/2017	<b>Supersedes date:</b>	10/01/2017
<b>Transportation version number:</b>	1.00 (10/01/2017)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

MB06, Mirror Bright Paste Wax (26-94A)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Automotive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF  
**Telephone:** +44 (0)870 241 6696  
**E Mail:** info@meguiars.co.uk  
**Website:** www.meguiars.co.uk

#### 1.4. Emergency telephone number

+44 (0)870 241 6696

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Flammable Solid, Category 1 - Flam. Sol. 1; H228  
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336  
Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

## MB06, Mirror Bright Paste Wax (26-94A)

### SIGNAL WORD

DANGER.

### Symbols:

GHS02 (Flame) |GHS07 (Exclamation mark) |

### Pictograms



### Ingredients:

Ingredient	CAS Nbr	% by Wt
Distillates (petroleum), hydrotreated light	64742-47-8	5 - 10

### HAZARD STATEMENTS:

H228	Flammable solid.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENTS

#### General:

P102 Keep out of reach of children.

#### Prevention:

P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261A Avoid breathing vapours.

#### Response:

P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P370 + P378G In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

9% of the mixture consists of components of unknown acute oral toxicity.

Contains 60% of components with unknown hazards to the aquatic environment.

#### Notes on labelling

H304 is not required on the label due to the product's viscosity  
Nota P applied to CAS 64742-48-9 and CAS 64741-65-7.

### 2.3. Other hazards

None known.

## SECTION 3: Composition/information on ingredients

**MB06, Mirror Bright Paste Wax (26-94A)**

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>EU Inventory</b>	<b>% by Wt</b>	<b>Classification</b>
Naphtha (petroleum), hydrotreated heavy	64742-48-9	265-150-3	30 - 60	Asp. Tox. 1, H304 - Nota P (CLP) Skin Irrit. 2, H315; STOT SE 3, H336 (Self Classified)
Kaolin, calcined	92704-41-1	296-473-8	10 - 30	Substance not classified as hazardous
Siloxanes and silicones, di-Me	63148-62-9		7 - 13	Substance not classified as hazardous
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	277-291-8	5 - 10	Substance not classified as hazardous
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8	5 - 10	Asp. Tox. 1, H304 (CLP) Aquatic Chronic 2, H411 (Vendor) Flam. Liq. 3, H226; STOT SE 3, H336; EUH066 (Self Classified)
Carnauba Wax	8015-86-9	232-399-4	1 - 5	Substance not classified as hazardous
Aluminium oxide	1344-28-1	215-691-6	1 - 5	Substance with a Community level exposure limit in the workplace
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	273-219-4	0.5 - 1.5	Substance not classified as hazardous
Benzyl Benzoate	120-51-4	204-402-9	< 0.5	Acute Tox. 4, H302; Aquatic Chronic 2, H411 (CLP)

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1 Information on toxicological effects

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

### 5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools.

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store

## MB06, Mirror Bright Paste Wax (26-94A)

away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Aluminium oxide	1344-28-1	UK HSC	TWA(as inhalable dust):10 mg/m <sup>3</sup> ;TWA(as respirable dust):4 mg/m <sup>3</sup>	
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Manufacturer determined	TWA:100 ppm	

UK HSC : UK Health and Safety Commission  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Eye protection not required.

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

##### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Appearance/Odour	Pleasant odor. Cream coloured paste.
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Boiling point/boiling range	$\geq 140.6$ °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Flammable Solid: Category 1. Flammable Solid: Category 1.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	65.6 °C [ <i>Test Method</i> :Pensky-Martens Closed Cup]
Autoignition temperature	<i>No data available.</i>
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Relative density	0.85 [ <i>Ref Std</i> :WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Density	0.85 g/cm <sup>3</sup>

### 9.2. Other information

Molecular weight	<i>No data available.</i>
------------------	---------------------------

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.

Sparks and/or flames.

### 10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

## 10.6 Hazardous decomposition products

### Substance

None known.

### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

May be harmful in contact with skin. Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

#### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

#### Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE <sub>2,000</sub> - 5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE <sub>20</sub> - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

**MB06, Mirror Bright Paste Wax (26-94A)**

Naphtha (petroleum), hydrotreated heavy	Inhalation-Vapour		LC50 estimated to be 20 - 50 mg/l
Naphtha (petroleum), hydrotreated heavy	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Ingestion	Rat	LD50 > 5,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Siloxanes and silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
Fatty acids, Montan-wax, Ethylene Esters	Dermal		LD50 estimated to be > 5,000 mg/kg
Fatty acids, Montan-wax, Ethylene Esters	Ingestion	Rat	LD50 > 2,000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Distillates (petroleum), hydrotreated light	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Carnauba Wax	Dermal		LD50 estimated to be > 5,000 mg/kg
Carnauba Wax	Ingestion	Rat	LD50 > 8,800 mg/kg
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Dermal		LD50 estimated to be > 5,000 mg/kg
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 12.6 mg/l
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Ingestion	Rat	LD50 > 5,000 mg/kg
Benzyl Benzoate	Dermal	Rabbit	LD50 4,000 mg/kg
Benzyl Benzoate	Ingestion	Rat	LD50 1,894 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Naphtha (petroleum), hydrotreated heavy	Rabbit	Irritant
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Aluminium oxide	Rabbit	No significant irritation
Carnauba Wax	Professional judgement	No significant irritation
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Rat	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Naphtha (petroleum), hydrotreated heavy	Rabbit	No significant irritation
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Aluminium oxide	Rabbit	No significant irritation
Carnauba Wax	Professional judgement	No significant irritation
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Rabbit	No significant irritation

**Skin Sensitisation**

Name	Species	Value
------	---------	-------



**MB06, Mirror Bright Paste Wax (26-94A)**

Naphtha (petroleum), hydrotreated heavy	Guinea pig	Not sensitising
Distillates (petroleum), hydrotreated light	Guinea pig	Not sensitising

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Naphtha (petroleum), hydrotreated heavy	In vivo	Not mutagenic
Naphtha (petroleum), hydrotreated heavy	In Vitro	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic
Aluminium oxide	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Naphtha (petroleum), hydrotreated heavy	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminium oxide	Inhalation	Rat	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Naphtha (petroleum), hydrotreated heavy	Inhalation	Not toxic to development	Rat	NOAEL 2.4 mg/l	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Naphtha (petroleum), hydrotreated heavy	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 6.5 mg/l	4 hours
Naphtha (petroleum), hydrotreated heavy	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), hydrotreated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional	NOAEL Not available	

**MB06, Mirror Bright Paste Wax (26-94A)**

				judgement		
--	--	--	--	-----------	--	--

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 4.6 mg/l	6 months
Naphtha (petroleum), hydrotreated heavy	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1.9 mg/l	13 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.6 mg/l	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	All data are negative	Rat	NOAEL 5.6 mg/l	12 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	heart	All data are negative	Multiple animal species	NOAEL 1.3 mg/l	90 days
Aluminium oxide	Inhalation	pneumoconiosis   pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

Name	Value
Naphtha (petroleum), hydrotreated heavy	Aspiration hazard
Distillates (petroleum), hydrotreated light	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Green algae	Estimated	72 hours	EC50	>100 mg/l
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl,	68953-58-2	Water flea	Estimated	48 hours	EC50	>100 mg/l

**MB06, Mirror Bright Paste Wax (26-94A)**

salts with bentonite						
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1		Data not available or insufficient for classification			
Benzyl Benzoate	120-51-4	Green Algae	Experimental	72 hours	EC50	0.475 mg/l
Benzyl Benzoate	120-51-4	Green Algae	Experimental	72 hours	NOEC	0.247 mg/l
Benzyl Benzoate	120-51-4	Gammarid scud	Experimental	96 hours	LC50	4.8 mg/l
Benzyl Benzoate	120-51-4	Rainbow trout	Experimental	96 hours	LC50	1.4 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9		Data not available or insufficient for classification			
Kaolin, calcined	92704-41-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Kaolin, calcined	92704-41-1	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Carnauba Wax	8015-86-9		Data not available or insufficient for classification			
Siloxanes and silicones, di-Me	63148-62-9		Data not available or insufficient for classification			
Distillates (petroleum), hydrotreated light	64742-47-8		Data not available or insufficient for classification			
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	EC50	1 mg/l
Distillates	64742-47-8	Rainbow trout	Estimated	96 hours	Lethal Level	2 mg/l

**MB06, Mirror Bright Paste Wax (26-94A)**

(petroleum), hydrotreated light					50%	
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	NOEC	>100 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Benzyl Benzoate	120-51-4	Experimental Biodegradation	28 days	BOD	90 % weight	OECD 301C - MITI test (I)
Kaolin, calcined	92704-41-1	Data not available or	N/A	N/A	N/A	N/A

**MB06, Mirror Bright Paste Wax (26-94A)**

		insufficient for classification				
Carnauba Wax	8015-86-9	Estimated Biodegradation	28 days	CO2 evolution	96 % weight	OECD 301B - Modified sturm or CO2
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Benzyl Benzoate	120-51-4	Estimated Photolysis		Photolytic half-life (in air)	4.3 days (t 1/2)	Other methods

**12.3 : Bioaccumulative potential**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Siloxanes and silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	Estimated Bioconcentration		Bioaccumulation factor	20.5	Other methods
Benzyl Benzoate	120-51-4	Estimated Bioconcentration		Bioaccumulation factor	48	Estimated: Bioconcentration factor
Carnauba Wax	8015-86-9	Estimated Bioconcentration		Bioaccumulation factor	7.4	Estimated: Bioconcentration factor
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

### 12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

### 12.6. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

### EU waste code (product as sold)

120109\* Machining emulsions and solutions free of halogens

## SECTION 14: Transportation information

ADR: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; (E); F1.

IMDG: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; EMS: FA, SG.

IATA: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact manufacturer for more information The components of this product are in compliance with the chemical notification requirements of TSCA.

### 15.2. Chemical Safety Assessment

Not applicable

## SECTION 16: Other information

### List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.

**MB06, Mirror Bright Paste Wax (26-94A)**

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision information:**

Section 12: Persistence and Degradability information information was modified.

Section 12:Biocumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

**Meguiar's, Inc. United Kingdom MSDSs are available at [www.meguiars.co.uk](http://www.meguiars.co.uk)**