



Safety Data Sheet

Copyright, 2018, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	36-4891-2	Version number:	3.01
Revision date:	05/07/2018	Supersedes date:	07/05/2018
Transportation version number:	1.00 (10/01/2017)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

MB06, Mirror Bright Paste Wax (26-94A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF
Telephone: +44 (0)870 241 6696
E Mail: info@meguiars.co.uk
Website: www.meguiars.co.uk

1.4. Emergency telephone number

+44 (0)870 241 6696

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Flammable Solid, Category 1 - Flam. Sol. 1; H228

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

MB06, Mirror Bright Paste Wax (26-94A)

Symbols:

GHS02 (Flame) |GHS09 (Environment) |

Pictograms



HAZARD STATEMENTS:

H228 Flammable solid.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

Prevention:

P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 Avoid release to the environment.

Response:

P370 + P378I In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SUPPLEMENTAL INFORMATION

Supplemental Hazard Statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

9% of the mixture consists of components of unknown acute oral toxicity.

Contains 17% of components with unknown hazards to the aquatic environment.

Notes on labelling

H304 is not required on the label due to the product's viscosity

Nota P applied to CAS 64741-65-7.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification

MB06, Mirror Bright Paste Wax (26-94A)

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics		920-901-0		30 - 60	Asp. Tox. 1, H304; EUH066
Kaolin, calcined	92704-41-1	296-473-8		10 - 30	Substance not classified as hazardous
Siloxanes and silicones, di-Me	63148-62-9			7 - 13	Substance not classified as hazardous
Organic Salt (NJTSRN 04499600-6842)	Trade Secret			5 - 10	Substance with a Community level exposure limit in the workplace
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	277-291-8		5 - 10	Substance not classified as hazardous
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8		< 10	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; Skin Irrit. 2, H315; STOT SE 3, H336
Carnauba Wax	8015-86-9	232-399-4		1 - 5	Substance not classified as hazardous
Aluminium oxide	1344-28-1	215-691-6		1 - 5	Substance with a Community level exposure limit in the workplace
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	273-219-4		0.5 - 1.5	Substance not classified as hazardous
Titanium dioxide	13463-67-7	236-675-5		< 0.3	Substance with a Community level exposure limit in the workplace

Note: Any entry in the EC# column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Aluminium oxide	1344-28-1	UK HSC	TWA(as inhalable dust):10 mg/m ³ ;TWA(as respirable dust):4 mg/m ³	
Titanium dioxide	13463-67-7	UK HSC	TWA(Inhalable):10 mg/m ³ ;TWA(respirable):4 mg/m ³	
Organic Salt (NJTSRN 04499600-6842)	Trade Secret	UK HSC	TWA:2 mg/m ³	

UK HSC : UK Health and Safety Commission
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Eye protection not required. Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
 Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
-----------------	-----------------------	--------------------------

MB06, Mirror Bright Paste Wax (26-94A)

Polymer laminate

No data available

No data available

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Paste
Appearance/Odour	Pleasant odor. Cream coloured paste.
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Boiling point/boiling range	≥ 140.6 °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Flammable Solid: Category 1. Flammable Solid: Category 1.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	65.6 °C [<i>Test Method</i> :Pensky-Martens Closed Cup]
Autoignition temperature	<i>No data available.</i>
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Relative density	0.85 [<i>Ref Std</i> :WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>No data available.</i>
Density	0.85 g/cm ³

9.2. Other information

EU Volatile Organic Compounds	<i>No data available.</i>
Molecular weight	<i>No data available.</i>
Percent volatile	51.4 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

MB06, Mirror Bright Paste Wax (26-94A)

the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Inhalation-Vapour		LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Siloxanes and silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
Fatty acids, Montan-wax, Ethylene Esters	Dermal		LD50 estimated to be > 5,000 mg/kg
Fatty acids, Montan-wax, Ethylene Esters	Ingestion	Rat	LD50 > 2,000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Distillates (petroleum), hydrotreated light	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Carnauba Wax	Dermal		LD50 estimated to be > 5,000 mg/kg
Carnauba Wax	Ingestion	Rat	LD50 > 8,800 mg/kg
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Dermal		LD50 estimated to be > 5,000 mg/kg
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 12.6 mg/l
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Rabbit	Minimal irritation
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Aluminium oxide	Rabbit	No significant irritation
Carnauba Wax	Professional judgement	No significant irritation
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Rat	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value

MB06, Mirror Bright Paste Wax (26-94A)

Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Rabbit	Mild irritant
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Aluminium oxide	Rabbit	No significant irritation
Carnauba Wax	Professional judgement	No significant irritation
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Guinea pig	Not classified
Distillates (petroleum), hydrotreated light	Guinea pig	Not classified
Titanium dioxide	Human and animal	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	In vivo	Not mutagenic
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic
Aluminium oxide	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not available	Not carcinogenic
Distillates (petroleum), hydrotreated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminium oxide	Inhalation	Rat	Not carcinogenic
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for female reproduction	Not available	NOAEL NA	1 generation
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for male reproduction	Not available	NOAEL NA	28 days
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for development	Not available	NOAEL NA	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

MB06, Mirror Bright Paste Wax (26-94A)

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), hydrotreated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), hydrotreated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Aspiration hazard
Distillates (petroleum), hydrotreated light	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Water flea	Estimated	48 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Green Algae	Estimated	72 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Rainbow trout	Estimated	96 hours	Lethal Level 50%	>1,000 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Green Algae	Estimated	72 hours	No obs Effect Level	1,000 mg/l
Kaolin, calcined	92704-41-1	Water flea	Estimated	48 hours	EC50	>100 mg/l
Kaolin, calcined	92704-41-1	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l

MB06, Mirror Bright Paste Wax (26-94A)

Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	EC50	2,500 mg/l
Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	Effect Concentration 10%	41 mg/l
Kaolin, calcined	92704-41-1	Rainbow trout	Estimated	30 days	NOEC	>100 mg/l
Siloxanes and silicones, di-Me	63148-62-9		Data not available or insufficient for classification			
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1		Data not available or insufficient for classification			
Distillates (petroleum), hydrotreated light	64742-47-8	Rainbow trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	EC50	1 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l
Organic Salt (NJTSRN 04499600-6842)	Trade Secret		Data not available or insufficient for classification			
Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	NOEC	>100 mg/l
Carnauba Wax	8015-86-9		Data not available or insufficient for classification			
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Water flea	Estimated	48 hours	EC50	>100 mg/l
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Green algae	Estimated	72 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Estimated Biodegradation	28 days	BOD	31.3 % BOD/ThBOD	OECD 301F - Manometric respirometry
Kaolin, calcined	92704-41-1	Data not available - insufficient			N/A	

MB06, Mirror Bright Paste Wax (26-94A)

Siloxanes and silicones, di-Me	63148-62-9	Data not available or insufficient			N/A	
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	Data not available or insufficient			N/A	
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient			N/A	
Organic Salt (NJTSRN 04499600-6842)	Trade Secret	Data not available or insufficient			N/A	
Aluminium oxide	1344-28-1	Data not available or insufficient			N/A	
Carnauba Wax	8015-86-9	Estimated Biodegradation	28 days	CO2 evolution	96 % weight	OECD 301B - Modified sturm or CO2
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Data not available or insufficient			N/A	
Titanium dioxide	13463-67-7	Data not available or insufficient			N/A	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fatty acids, Montan-wax, Ethylene Esters	73138-45-1	Estimated Bioconcentration		Bioaccumulation factor	20.5	Other methods
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Organic Salt (NJTSRN 04499600-6842)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carnauba Wax	8015-86-9	Estimated Bioconcentration		Bioaccumulation factor	7.4	Estimated: Bioconcentration factor
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulation factor	9.6	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

120109* Machining emulsions and solutions free of halogens

SECTION 14: Transportation information

ADR: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; (E); F1.

IMDG: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II; EMS: FA, SG.

IATA: UN1325; Flammable Solid, Organic, N.O.S. (Hydrotreated Heavy Naphtha (Petroleum) and Hydrotreated Light Petroleum Distillates); 4.1; II.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Global inventory status

Contact manufacturer for more information This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066 Repeated exposure may cause skin dryness or cracking.
H226 Flammable liquid and vapour.

H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

Section 11: Acute Toxicity table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Health Effects - Ingestion information information was modified.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 15: Chemical Safety Assessment information was added.
Section 15: Regulations - Inventories information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. United Kingdom SDSs are available at www.meguiars.co.uk