



Safety Data Sheet

Copyright, 2015, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 33-4677-2 **Version number:** 1.00
Revision date: 22/06/2015 **Supersedes date:** Initial issue.
Transportation version number: 1.00 (22/06/2015)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

M4965, Marine & RV Fiberglass Restoration System

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Marine

1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF
Telephone: +44 (0)870 241 6696
E Mail: info@meguiars.co.uk
Website: www.meguiars.co.uk

1.4. Emergency telephone number

+44 (0)870 241 6696

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

26-8180-7, 33-1945-6, 26-6666-7

TRANSPORTATION INFORMATION

ADR/IATA/IMDG: See kit components for transport information.

KIT LABEL

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols:

GHS07 (Exclamation mark) |

Pictograms



HAZARD STATEMENTS:

H315 Causes skin irritation.

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

Response:

P332 + P313 If skin irritation occurs: Get medical advice/attention.

EUH208 Contains Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Notes on labelling

H304 is not required on the label due to the product's viscosity

Nota P applied to CAS 64742-48-9 and 8052-41-3.

Revision information:

No revision information is available.



Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	26-6666-7	Version number:	4.02
Revision date:	06/10/2017	Supersedes date:	16/06/2017
Transportation version number:	1.00 (10/08/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

M56, Boat/RV Pure Liquid Wax (26-65B): M5601, M5616

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Marine

1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF
Telephone: +44 (0)870 241 6696
E Mail: info@meguiars.co.uk
Website: www.meguiars.co.uk

1.4. Emergency telephone number

+44 (0)870 241 6696

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373
Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols:

GHS07 (Exclamation mark) | GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	265-191-7	< 10

HAZARD STATEMENTS:

H315	Causes skin irritation.	
H373	May cause damage to organs through prolonged or repeated exposure:	nervous system
H412	Harmful to aquatic life with long lasting effects.	

PRECAUTIONARY STATEMENTS

General:

P102 Keep out of reach of children.

Prevention:

P260A Do not breathe vapours.

Response:

P332 + P313 If skin irritation occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SUPPLEMENTAL INFORMATION

Supplemental Hazard Statements:

EUH208 Contains Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

1% of the mixture consists of components of unknown acute oral toxicity.

Contains 1% of components with unknown hazards to the aquatic environment.

Information required per Regulation (EU) No 528/2012 on Biocidal Products:

Contains a biocidal product: Contains C(M)IT/MIT (3:1). May produce an allergic reaction.

Notes on labelling

H304 is not required on the label due to the product's viscosity

Nota P applied to CAS 64742-48-9 and CAS 8052-41-3.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Non-Hazardous Ingredients	7732-18-5	231-791-2		40 - 70	Substance not classified as hazardous
Kaolin, calcined	92704-41-1	296-473-8		5 - 10	Substance not classified as hazardous
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	265-191-7		< 10	Asp. Tox. 1, H304; STOT RE 1, H372 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; Skin Irrit. 2, H315
Naphtha (petroleum), hydrotreated heavy	64742-48-9	265-150-3		3 - 7	Asp. Tox. 1, H304 - Nota P Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8		3 - 7	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; Skin Irrit. 2, H315; STOT SE 3, H336
Siloxanes and silicones, di-Me	63148-62-9			1 - 5	Substance not classified as hazardous
Conditioners	Trade Secret			1 - 5	Substance not classified as hazardous
Synthetic Hydrocarbon Mixture (NJRTK # 80100348-5009P)	Trade Secret			0.5 - 1.5	Substance not classified as hazardous
White Mineral Oil (Petroleum)	8042-47-5	232-455-8		0.5 - 1.5	Asp. Tox. 1, H304
Stoddard solvent	8052-41-3	232-489-3		0.1 - 1	Asp. Tox. 1, H304; STOT RE 1, H372 - Nota P Skin Irrit. 2, H315
Titanium dioxide	13463-67-7	236-675-5		< 0.05	Substance with a Community level exposure limit in the workplace
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9			< 0.002	Acute Tox. 3, H331; Acute Tox. 3, H311; Acute Tox. 3, H301; Skin Corr. 1B, H314; Skin Sens. 1A, H317; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

No need for first aid is anticipated.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent

M56, Boat/RV Pure Liquid Wax (26-65B): M5601, M5616

material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Titanium dioxide	13463-67-7	UK HSC	TWA(Inhalable):10 mg/m ³ ;TWA(respirable):4 mg/m ³	
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Manufacturer determined	TWA:100 ppm	

UK HSC : UK Health and Safety Commission
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the

M56, Boat/RV Pure Liquid Wax (26-65B): M5601, M5616

results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Appearance/Odour	Banana fragrance; Light yellow lotion
Odour threshold	No data available.
pH	7.5 - 8.5
Boiling point/boiling range	198.9 °C
Melting point	Not applicable.
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	Flash point > 93 °C (200 °F)
Autoignition temperature	No data available.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Relative density	0.95 [Ref Std: WATER=1]
Water solubility	Moderate
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Evaporation rate	No data available.
Vapour density	No data available.
Decomposition temperature	No data available.
Viscosity	25,000 - 37,000 mPa-s
Density	0.95 g/cm ³

9.2. Other information

EU Volatile Organic Compounds No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Temperatures above the boiling point.

10.5 Incompatible materials

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

M56, Boat/RV Pure Liquid Wax (26-65B): M5601, M5616

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Solvent naphtha (petroleum), medium aliphatic	Inhalation-Vapour		LC50 estimated to be 20 - 50 mg/l
Solvent naphtha (petroleum), medium aliphatic	Dermal	Rabbit	LD50 > 3,000 mg/kg
Solvent naphtha (petroleum), medium aliphatic	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Distillates (petroleum), hydrotreated light	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Inhalation-Vapour		LC50 estimated to be 20 - 50 mg/l
Naphtha (petroleum), hydrotreated heavy	Dermal	Rabbit	LD50 > 3,000 mg/kg
Naphtha (petroleum), hydrotreated heavy	Ingestion	Rat	LD50 > 5,000 mg/kg
Siloxanes and silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
Conditioners	Dermal		LD50 estimated to be > 5,000 mg/kg
Conditioners	Ingestion	Rat	LD50 > 8,800 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Stoddard solvent	Inhalation-Vapour		LC50 estimated to be 20 - 50 mg/l
Stoddard solvent	Dermal	Rabbit	LD50 > 3,000 mg/kg
Stoddard solvent	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Dermal	Rabbit	LD50 87 mg/kg
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Solvent naphtha (petroleum), medium aliphatic	Rabbit	Irritant
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Naphtha (petroleum), hydrotreated heavy	Rabbit	Irritant
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Conditioners	Professional judgement	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	No significant irritation
Stoddard solvent	Rabbit	Irritant
Titanium dioxide	Rabbit	No significant irritation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Rabbit	Corrosive

M56, Boat/RV Pure Liquid Wax (26-65B): M5601, M5616**Serious Eye Damage/Irritation**

Name	Species	Value
Solvent naphtha (petroleum), medium aliphatic	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Naphtha (petroleum), hydrotreated heavy	Rabbit	No significant irritation
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
Conditioners	Professional judgement	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	Mild irritant
Stoddard solvent	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Solvent naphtha (petroleum), medium aliphatic	Guinea pig	Not classified
Distillates (petroleum), hydrotreated light	Guinea pig	Not classified
Naphtha (petroleum), hydrotreated heavy	Guinea pig	Not classified
White Mineral Oil (Petroleum)	Guinea pig	Not classified
Stoddard solvent	Guinea pig	Not classified
Titanium dioxide	Human and animal	Not classified
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Human and animal	Sensitising

Photosensitisation

Name	Species	Value
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Human and animal	Not sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Solvent naphtha (petroleum), medium aliphatic	In vivo	Not mutagenic
Solvent naphtha (petroleum), medium aliphatic	In Vitro	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic
Naphtha (petroleum), hydrotreated heavy	In vivo	Not mutagenic
Naphtha (petroleum), hydrotreated heavy	In Vitro	Some positive data exist, but the data are not sufficient for classification
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic
Stoddard solvent	In vivo	Not mutagenic
Stoddard solvent	In Vitro	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	In vivo	Not mutagenic

M56, Boat/RV Pure Liquid Wax (26-65B): M5601, M5616

one		
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Solvent naphtha (petroleum), medium aliphatic	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Solvent naphtha (petroleum), medium aliphatic	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Naphtha (petroleum), hydrotreated heavy	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Stoddard solvent	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Stoddard solvent	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Dermal	Mouse	Not carcinogenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Solvent naphtha (petroleum), medium aliphatic	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
Naphtha (petroleum), hydrotreated heavy	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
White Mineral Oil (Petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Stoddard solvent	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

M56, Boat/RV Pure Liquid Wax (26-65B): M5601, M5616

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Solvent naphtha (petroleum), medium aliphatic	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Solvent naphtha (petroleum), medium aliphatic	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Solvent naphtha (petroleum), medium aliphatic	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Solvent naphtha (petroleum), medium aliphatic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), hydrotreated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Naphtha (petroleum), hydrotreated heavy	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Stoddard solvent	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Stoddard solvent	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Stoddard solvent	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Stoddard solvent	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Solvent naphtha (petroleum), medium aliphatic	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Solvent naphtha (petroleum), medium aliphatic	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Solvent naphtha	Inhalation	respiratory system	Not classified	Multiple	NOAEL 0.6	90 days

M56, Boat/RV Pure Liquid Wax (26-65B): M5601, M5616

(petroleum), medium aliphatic				animal species	mg/l	
Solvent naphtha (petroleum), medium aliphatic	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Solvent naphtha (petroleum), medium aliphatic	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Naphtha (petroleum), hydrotreated heavy	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Naphtha (petroleum), hydrotreated heavy	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Naphtha (petroleum), hydrotreated heavy	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
White Mineral Oil (Petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil (Petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Stoddard solvent	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Stoddard solvent	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Stoddard solvent	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Stoddard solvent	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Stoddard solvent	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
Solvent naphtha (petroleum), medium aliphatic	Aspiration hazard
Distillates (petroleum), hydrotreated light	Aspiration hazard
Naphtha (petroleum), hydrotreated heavy	Aspiration hazard
White Mineral Oil (Petroleum)	Aspiration hazard
Stoddard solvent	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

M56, Boat/RV Pure Liquid Wax (26-65B): M5601, M5616
12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Kaolin, calcined	92704-41-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Kaolin, calcined	92704-41-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Kaolin, calcined	92704-41-1	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Rainbow trout	Estimated	96 hours	Lethal Level 50%	20 mg/l
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Green Algae	Estimated	72 hours	Effect Level 50%	8.3 mg/l
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Green Algae	Estimated	72 hours	No obs Effect Level	4 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Rainbow trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	EC50	1 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Water flea	Estimated	48 hours	Effect Level 50%	4.5 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Fathead minnow	Estimated	96 hours	Lethal Level 50%	8.2 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Green Algae	Estimated	72 hours	Effect Level 50%	3.1 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Green Algae	Estimated	72 hours	No obs Effect Level	0.5 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Water flea	Estimated	21 days	No obs Effect Level	2.6 mg/l
Conditioners	Trade Secret		Data not available or insufficient for classification			
Siloxanes and silicones, di-Me	63148-62-9		Data not available or insufficient for classification			
White Mineral Oil (Petroleum)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l
Stoddard solvent	8052-41-3		Data not available or insufficient for classification			

M56, Boat/RV Pure Liquid Wax (26-65B): M5601, M5616

Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Diatom	Experimental	72 hours	EC50	0.021 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Water flea	Experimental	48 hours	EC50	0.18 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Diatom	Experimental	72 hours	NOEC	0.01 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Experimental Biodegradation	28 days	CO2 evolution	55 % weight	OECD 301B - Modified sturm or CO2
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Naphtha (petroleum), hydrotreated heavy	64742-48-9	Estimated Biodegradation	28 days	BOD	10 % BOD/ThBOD	OECD 301D - Closed bottle test
Conditioners	Trade Secret	Estimated Biodegradation	28 days	CO2 evolution	96 % weight	OECD 301B - Modified sturm or CO2
Siloxanes and silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White Mineral Oil (Petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Stoddard solvent	8052-41-3	Experimental Biodegradation	28 days	CO2 evolution	63 % weight	OECD 301B - Modified sturm or CO2
Stoddard solvent	8052-41-3	Estimated Photolysis		Photolytic half-life (in air)	6.49 days (t 1/2)	Other methods
Titanium dioxide	13463-67-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

M56, Boat/RV Pure Liquid Wax (26-65B): M5601, M5616

Naphtha (petroleum), hydrotreated heavy	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Conditioners	Trade Secret	Estimated Bioconcentration		Bioaccumulation factor	7.4	Estimated: Bioconcentration factor
Siloxanes and silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White Mineral Oil (Petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Stoddard solvent	8052-41-3	Estimated Bioconcentration		Bioaccumulation factor	1944	Estimated: Bioconcentration factor
Titanium dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulation factor	9.6	Other methods
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

120112* Spent waxes and fats

SECTION 14: Transportation information

ADR/IMDG/IATA: Not restricted for transport.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Carcinogenicity

Ingredient

Titanium dioxide

CAS Nbr

13463-67-7

Classification

Grp. 2B: Possible human
carc.

Regulation

International Agency
for Research on Cancer

Global inventory status

Contact manufacturer for more information The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

CLP: Ingredient table information was modified.

Label: CLP Percent Unknown information was modified.

Label: CLP Precautionary - Prevention information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 4: First aid for eye contact information information was modified.

Section 5: Fire - Advice for fire fighters information information was modified.

Section 8: glove data value information was deleted.

Section 8: glove data value information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 8: Personal Protection - Skin/hand information information was modified.

Section 9: No Data Available Statement information was deleted.

Section 9: Property description for optional properties information was added.

Section 11: Acute Toxicity table information was modified.

Section 11: Aspiration Hazard Table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

Section 13: Standard Phrase Category Waste GHS information was modified.

Section 15: Carcinogenicity information information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. United Kingdom MSDSs are available at www.meguiars.co.uk



Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	26-8180-7	Version number:	4.00
Revision date:	11/12/2017	Supersedes date:	16/06/2017
Transportation version number:	1.00 (12/07/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

M49, Hard Water Oxidation Remover (11-83D): M4916, M4901

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Marine

1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF
Telephone: +44 (0)870 241 6696
E Mail: info@meguiars.co.uk
Website: www.meguiars.co.uk

1.4. Emergency telephone number

+44 (0)870 241 6696

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

Not applicable

SUPPLEMENTAL INFORMATION

Supplemental Hazard Statements:

M49, Hard Water Oxidation Remover (11-83D): M4916, M4901

EUH208

Contains Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

Information required per Regulation (EU) No 528/2012 on Biocidal Products:

Contains a biocidal product: Contains C(M)IT/MIT (3:1). May produce an allergic reaction.

Notes on labellingUpdated per Regulation (EC) No. 648/2004 on detergents. H304 is not required on the label due to the product's viscosity
Ingredient required per 648/2004 (not required on industrial label): <5%: Anionic surfactant. Contains: Colorant, Mixture of Methylchloroisothiazolinone and Methylisothiazolinone (3:1).

Nota N applied to CAS# 64742-14-9.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Non-Hazardous Ingredients	Mixture			40 - 60	Substance not classified as hazardous
Aluminium Oxide (non-fibrous)	1344-28-1	215-691-6		10 - 30	Substance with a Community level exposure limit in the workplace
Distillates (petroleum), acid-treated light	64742-14-9	265-114-7		10 - 15	Nota N Asp. Tox. 1, H304; STOT SE 3, H336; EUH066
White mineral oil (petroleum)	8042-47-5	232-455-8		1 - 5	Asp. Tox. 1, H304
Sorbitan, (Z)-9-octadecenoate (2:3)	8007-43-0	232-360-1		0.5 - 1.5	Substance not classified as hazardous
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9			< 0.001	Acute Tox. 3, H331; Acute Tox. 3, H311; Acute Tox. 3, H301; Skin Corr. 1B, H314; Skin Sens. 1A, H317; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

No need for first aid is anticipated.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Irritant vapours or gases.

Condition

During combustion.

During combustion.

During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Vapours may travel long distances along the ground or floor to an ignition source and flash back.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Aluminium Oxide (non-fibrous)	1344-28-1	UK HSC	TWA(as inhalable dust):10 mg/m ³ ;TWA(as respirable dust):4 mg/m ³	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

M49, Hard Water Oxidation Remover (11-83D): M4916, M4901

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Appearance/Odour	Sweet odour; White, viscous, semi-pourable lotion
Odour threshold	No data available.
pH	Not applicable.
Boiling point/boiling range	198.9 °C
Melting point	Not applicable.
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	> 93.3 °C [Test Method:Pensky-Martens Closed Cup] [Details:D93-90]
Autoignition temperature	No data available.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Relative density	1 [Ref Std:WATER=1]
Water solubility	Negligible
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Evaporation rate	No data available.
Vapour density	No data available.
Decomposition temperature	No data available.
Viscosity	8,000 - 16,000 mPa-s
Density	1 g/cm ³

9.2. Other information

EU Volatile Organic Compounds No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Temperatures above the boiling point.

10.5 Incompatible materials

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminium Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium Oxide (non-fibrous)	Inhalation-Dust/Mist	Rat	LC50 > 2.3 mg/l

M49, Hard Water Oxidation Remover (11-83D): M4916, M4901

	(4 hours)		
Aluminium Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (petroleum), acid-treated light	Dermal	Rabbit	LD50 > 2,000 mg/kg
Distillates (petroleum), acid-treated light	Ingestion	Rat	LD50 > 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Dermal	Rabbit	LD50 87 mg/kg
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
Distillates (petroleum), acid-treated light	Professional judgement	Mild irritant
White mineral oil (petroleum)	Rabbit	No significant irritation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
Distillates (petroleum), acid-treated light	Professional judgement	Mild irritant
White mineral oil (petroleum)	Rabbit	Mild irritant
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Distillates (petroleum), acid-treated light	Guinea pig	Not classified
White mineral oil (petroleum)	Guinea pig	Not classified
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Human and animal	Sensitising

Photosensitisation

Name	Species	Value
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Human and animal	Not sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value

M49, Hard Water Oxidation Remover (11-83D): M4916, M4901

Aluminium Oxide (non-fibrous)	In Vitro	Not mutagenic
Distillates (petroleum), acid-treated light	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	In vivo	Not mutagenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Aluminium Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Distillates (petroleum), acid-treated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Dermal	Mouse	Not carcinogenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity
Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), acid-treated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), acid-treated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), acid-treated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

M49, Hard Water Oxidation Remover (11-83D): M4916, M4901**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminium Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium Oxide (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days

Aspiration Hazard

Name	Value
Distillates (petroleum), acid-treated light	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1		Experimental	96 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Distillates (petroleum), acid-treated light	64742-14-9		Insufficient to classify			
Distillates (petroleum), acid-treated light	64742-14-9		Data not available or insufficient for classification			
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
Sorbitan, (Z)-9-octadecenoate (2:3)	8007-43-0	Fish other	Laboratory	96 hours	LC50	>100 mg/l
Sorbitan, (Z)-9-octadecenoate (2:3)	8007-43-0	Copepods	Experimental	48 hours	EC50	>7,756 mg/l

M49, Hard Water Oxidation Remover (11-83D): M4916, M4901

Sorbitan, (Z)-9-octadecenoate (2:3)	8007-43-0	Diatom	Experimental	72 hours	EC50	1,916 mg/l
Sorbitan, (Z)-9-octadecenoate (2:3)	8007-43-0	Water flea	Experimental	21 days	NOEC	>100 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Water flea	Experimental	48 hours	EC50	0.18 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Diatom	Experimental	72 hours	EC50	0.021 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Diatom	Experimental	72 hours	NOEC	0.01 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminium Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), acid-treated light	64742-14-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Sorbitan, (Z)-9-octadecenoate (2:3)	8007-43-0	Estimated Biodegradation	28 days	CO2 evolution	85 % weight	OECD 301B - Modified sturm or CO2
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminium Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), acid-treated light	64742-14-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Sorbitan, (Z)-9-octadecenoate (2:3)	8007-43-0	Estimated Bioconcentration		Log Kow	22.56	Other methods
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

M49, Hard Water Oxidation Remover (11-83D): M4916, M4901

The surfactant(s) contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

20 01 30 Detergents other than those mentioned in 20 01 29.

SECTION 14: Transportation information

ADR/IMDG/IATA: Not restricted for transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact manufacturer for more information The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Revision information:

Section 3: Composition/ Information of ingredients table information was modified.

Section 4: First aid for eye contact information information was modified.
Section 5: Fire - Advice for fire fighters information information was modified.
Section 5: Fire - Extinguishing media information information was modified.
Section 6: Accidental release personal information information was modified.
Section 8: Eye protection information information was added.
Section 8: Eye/face protection information information was deleted.
Section 8: glove data value information was modified.
Section 8: Occupational exposure limit table information was modified.
Section 8: Personal Protection - Eye information information was deleted.
Section 8: Personal Protection - Skin/hand information information was modified.
Section 9: No Data Available Statement information was deleted.
Section 9: Property description for optional properties information was added.
Section 11: Acute Toxicity table information was modified.
Section 11: Aspiration Hazard Table information was modified.
Section 11: Carcinogenicity Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 11: Target Organs - Single Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Section 13: Standard Phrase Category Waste GHS information was modified.
Section 15: Label remarks and EU Detergent information was modified.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. United Kingdom MSDSs are available at www.meguiars.co.uk



Safety Data Sheet

Copyright, 2017, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	33-1945-6	Version number:	2.02
Revision date:	20/06/2017	Supersedes date:	20/09/2016
Transportation version number:	1.00 (05/06/2015)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

M45, Marine Boat Polish (26-16A) : M4516

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Marine

1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF
Telephone: +44 (0)870 241 6696
E Mail: info@meguiars.co.uk
Website: www.meguiars.co.uk

1.4. Emergency telephone number

+44 (0)870 241 6696

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

Not applicable

SUPPLEMENTAL INFORMATION

Supplemental Hazard Statements:

M45, Marine Boat Polish (26-16A) : M4516

EUH208 Contains 3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone. May produce an allergic reaction.

2% of the mixture consists of components of unknown acute oral toxicity.

Contains 2% of components with unknown hazards to the aquatic environment.

Notes on labelling

H304 not required due to product viscosity.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Non-Hazardous Ingredients	7732-18-5	231-791-2		50 - 70	Substance not classified as hazardous
Kaolin, calcined	92704-41-1	296-473-8		7 - 13	Substance not classified as hazardous
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8		7 - 13	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; STOT SE 3, H336; EUH066
White Mineral Oil	8042-47-5	232-455-8		5 - 10	Asp. Tox. 1, H304
Conditioners	Trade Secret			< 5	Substance not classified as hazardous
Glycerin	56-81-5	200-289-5		1 - 5	Substance with a Community level exposure limit in the workplace
PEG Stearate	9004-99-3			0.45 - 0.5	Aquatic Acute 1, H400,M=1; Aquatic Chronic 3, H412
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	55965-84-9			0.001215 - 0.001485	Acute Tox. 3, H331; Acute Tox. 3, H311; Acute Tox. 3, H301; Skin Corr. 1B, H314; Skin Sens. 1A, H317; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

No need for first aid is anticipated.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons.
Carbon monoxide.
Carbon dioxide.

Condition

During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from areas where product may come into contact with food or pharmaceuticals.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Glycerin	56-81-5	UK HSC	TWA(as mist):10 mg/m ³	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Neoprene.	No data available	No data available

Respiratory protection

Wear respiratory protection if ventilation is inadequate to prevent overexposure. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program.

Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Appearance/Odour	Pleasant sweet odour; White viscous lotion
Odour threshold	<i>No data available.</i>
pH	6 - 6.75
Boiling point/boiling range	198.9 °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	Flash point > 93 °C (200 °F)
Autoignition temperature	<i>No data available.</i>
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Relative density	0.98 [Ref Std: WATER=1]
Water solubility	Moderate
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	2,500 - 8,500 mPa-s
Density	1 - 1.03 g/cm ³

9.2. Other information

Data is not available for other physical and chemical parameters.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong acids.
Strong bases.
Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

Eye contact

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Distillates (petroleum), hydrotreated light	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg

M45, Marine Boat Polish (26-16A) : M4516

White Mineral Oil	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil	Ingestion	Rat	LD50 > 5,000 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Dermal	Rabbit	LD50 87 mg/kg
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
White Mineral Oil	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
White Mineral Oil	Rabbit	Mild irritant
Glycerin	Rabbit	No significant irritation
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Distillates (petroleum), hydrotreated light	Guinea pig	Not classified
White Mineral Oil	Guinea pig	Not classified
Glycerin	Guinea pig	Not classified
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Human and animal	Sensitising

Photosensitisation

Name	Species	Value
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Human and animal	Not sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic
White Mineral Oil	In Vitro	Not mutagenic
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	In vivo	Not mutagenic
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	In Vitro	Some positive data exist, but the data are not

M45, Marine Boat Polish (26-16A) : M4516

Isothiazolone		sufficient for classification
---------------	--	-------------------------------

Carcinogenicity

Name	Route	Species	Value
Distillates (petroleum), hydrotreated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
White Mineral Oil	Dermal	Mouse	Not carcinogenic
White Mineral Oil	Inhalation	Multiple animal species	Not carcinogenic
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Dermal	Mouse	Not carcinogenic
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity
Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
White Mineral Oil	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), hydrotreated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), hydrotreated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

M45, Marine Boat Polish (26-16A) : M4516

Isothiazolone						
---------------	--	--	--	--	--	--

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
White Mineral Oil	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Glycerin	Inhalation	respiratory system heart liver kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years

Aspiration Hazard

Name	Value
Distillates (petroleum), hydrotreated light	Aspiration hazard
White Mineral Oil	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Glycerin	56-81-5	Water flea	Experimental	24 hours	EC50	>10,000 mg/l
Glycerin	56-81-5	Goldfish	Experimental	24 hours	LC50	>5,000 mg/l
PEG Stearate	9004-99-3	Zebra Fish	Estimated	96 hours	LC50	0.65 mg/l
PEG Stearate	9004-99-3	Green algae	Estimated	72 hours	EC50	0.64 mg/l
PEG Stearate	9004-99-3	Water flea	Estimated	48 hours	EC50	0.72 mg/l
PEG Stearate	9004-99-3	Green algae	Estimated	72 hours	NOEC	0.25 mg/l
Kaolin, calcined	92704-41-1		Data not available or insufficient for classification			
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	55965-84-9	Rainbow trout	Experimental	96 hours	LC50	0.07 mg/l
3(2H)-	55965-84-9	Green algae	Experimental	96 hours	EC50	0.062 mg/l

M45, Marine Boat Polish (26-16A) : M4516

Isothiazolone, 5-Chloro-2- Methyl-, Mixt. With 2-Methyl- 3(2H)- Isothiazolone						
3(2H)- Isothiazolone, 5-Chloro-2- Methyl-, Mixt. With 2-Methyl- 3(2H)- Isothiazolone	55965-84-9	Water flea	Experimental	48 hours	EC50	0.18 mg/l
3(2H)- Isothiazolone, 5-Chloro-2- Methyl-, Mixt. With 2-Methyl- 3(2H)- Isothiazolone	55965-84-9	Water flea	Experimental	21 days	NOEC	0.172 mg/l
White Mineral Oil	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
White Mineral Oil	8042-47-5	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l
White Mineral Oil	8042-47-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
White Mineral Oil	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Rainbow trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	EC50	1 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Kaolin, calcined	92704-41-1	Data not available or insufficient for	N/A	N/A	N/A	N/A

M45, Marine Boat Polish (26-16A) : M4516

		classification				
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
PEG Stearate	9004-99-3	Estimated Biodegradation	28 days	CO2 evolution	85.3 % weight	OECD 301B - Modified sturm or CO2
White Mineral Oil	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Glycerin	56-81-5	Experimental Biodegradation	14 days	BOD	63 % weight	OECD 301C - MITI test (I)
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	55965-84-9	Experimental Biodegradation	28 days	CO2 evolution	48 % weight	Other methods
Non-Hazardous Ingredients	7732-18-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
PEG Stearate	9004-99-3	Estimated Bioconcentration		Bioaccumulation factor	5.5	Estimated: Bioconcentration factor
White Mineral Oil	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerin	56-81-5	Experimental Bioconcentration		Log Kow	-1.76	Other methods
3(2H)-Isothiazolone, 5-Chloro-2-Methyl-, Mixt. With 2-Methyl-3(2H)-Isothiazolone	55965-84-9	Estimated Bioconcentration		Log Kow	0.5	Other methods
Non-Hazardous Ingredients	7732-18-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

20 01 30 Detergents other than those mentioned in 20 01 29.

SECTION 14: Transportation information

ADR/IATA/IMDG: Not restricted for transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact manufacturer for more information The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Label: CLP Percent Unknown information was added.
Section 3: Composition/ Information of ingredients table information was added.
Section 3: Composition/ Information of ingredients table information was deleted.
Section 9: Density information information was added.
Section 9: pH information information was added.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. United Kingdom MSDSs are available at www.meguiars.co.uk