



Safety Data Sheet

Copyright, 2019, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	38-3347-2	Version number:	1.00
Revision date:	28/01/2019	Supersedes date:	Initial issue.
Transportation version number:	1.00 (28/01/2019)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF
Telephone: +44 (0)870 241 6696
E Mail: info@meguiars.co.uk
Website: www.meguiars.co.uk

1.4. Emergency telephone number

+44 (0)870 241 6696

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

Not applicable

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

EUH208

Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1). May produce an allergic reaction.

Information required per Regulation (EU) No 528/2012 on Biocidal Products:

Contains a biocidal product: Contains C(M)IT/MIT (3:1). May produce an allergic reaction.

Notes on labelling

Updated per Regulation (EC) No. 648/2004 on detergents.

Ingredients required per 648/2004 (not required on industrial label): <5%: Anionic surfactants, non-ionic surfactants.

Contains: Mixture of Methylchloroisothiazolinone and Methylisothiazolinone.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Non hazardous ingredients	Mixture			60 - 100	Substance not classified as hazardous
Acetic acid, mercapto-, monoammonium salt	5421-46-5	226-540-9		10 - 30	Substance not classified as hazardous
Fatty Alcohol Ether Sulfate	Trade Secret			1 - 5	Substance not classified as hazardous
2-(2-Ethoxyethoxy)ethanol	111-90-0	203-919-7		1 - 5	Substance not classified as hazardous
Sodium xylenesulphonate	1300-72-7	215-090-9		1 - 5	Substance not classified as hazardous
Sulphuric acid, mono-C10-16-alkyl esters, sodium salts	68585-47-7	271-557-7		1 - 5	Skin Irrit. 2, H315; Eye Dam. 1, H318; STOT SE 3, H335
2-Butoxyethanol	111-76-2	203-905-0		1 - 5	Acute Tox. 4, H332; Acute Tox. 4, H312; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319
Alcohols, C12-16, ethoxylated	68551-12-2	500-221-7		<= 0.5	Eye Dam. 1, H318; Aquatic Acute 1, H400,M=1; Aquatic Chronic 2, H411
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	55965-84-9	911-418-6		< 0.0015	Acute Tox. 3, H301; Skin Corr. 1B, H314; Skin Sens. 1A, H317; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1 EUH071 Acute Tox. 2, H330; Acute Tox. 2, H310

Note: Any entry in the EC# column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
2-Butoxyethanol	111-76-2	UK HSC	TWA:123 mg/m ³ (25 ppm);STEL:246 mg/m ³ (50 ppm)	SKIN

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
2-Butoxyethanol	111-76-2	UK EH40 BMGVs	Butoxyacetic acid	Creatinine in urine	EOS	240 mmol/mol	

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EOS: End of shift.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.
Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Appearance/Odour	Sulfurous Odor, Orange/Red, Liquid
Odour threshold	<i>No data available.</i>
pH	6.3 - 7
Boiling point/boiling range	100 °C
Melting point	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	Flash point > 93 °C (200 °F)
Autoignition temperature	<i>No data available.</i>
Flammable Limits(LEL)	<i>No data available.</i>

Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Relative density	1.05 [Ref Std: WATER=1]
Water solubility	Complete
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Evaporation rate	No data available.
Vapour density	No data available.
Decomposition temperature	No data available.
Viscosity	20 - 80 mPa-s
Density	1.05 g/cm ³

9.2. Other information

EU Volatile Organic Compounds	No data available.
Molecular weight	No data available.
Percent volatile	77.5 % weight [Test Method: Estimated]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Light.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE300 - 2,000 mg/kg
2-(2-Ethoxyethoxy)ethanol	Dermal	Rabbit	LD50 9,143 mg/kg
2-(2-Ethoxyethoxy)ethanol	Ingestion	Rat	LD50 5,400 mg/kg
Sodium xylenesulphonate	Dermal		LD50 estimated to be > 5,000 mg/kg
Sodium xylenesulphonate	Ingestion	Rat	LD50 > 5,000 mg/kg
Sulphuric acid, mono-C10-16-alkyl esters, sodium salts	Dermal	Rat	LD50 > 2,000 mg/kg
Sulphuric acid, mono-C10-16-alkyl esters, sodium salts	Ingestion	Rat	LD50 977 mg/kg
2-Butoxyethanol	Dermal	Guinea pig	LD50 > 2,000 mg/kg
2-Butoxyethanol	Inhalation-Vapour (4 hours)	Guinea pig	LC50 > 2.6 mg/l
2-Butoxyethanol	Ingestion	Guinea pig	LD50 1,414 mg/kg
Alcohols, C12-16, ethoxylated	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.6 mg/l
Alcohols, C12-16, ethoxylated	Dermal	similar compounds	LD50 2,525 mg/kg
Alcohols, C12-16, ethoxylated	Ingestion	similar compounds	LD50 2,525 mg/kg
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Dermal	Rabbit	LD50 87 mg/kg
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
------	---------	-------

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

2-(2-Ethoxyethoxy)ethanol	Rabbit	No significant irritation
Sulphuric acid, mono-C10-16-alkyl esters, sodium salts	Rabbit	Irritant
2-Butoxyethanol	Rabbit	Irritant
Alcohols, C12-16, ethoxylated	Rat	No significant irritation
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
2-(2-Ethoxyethoxy)ethanol	Rabbit	Moderate irritant
Sulphuric acid, mono-C10-16-alkyl esters, sodium salts	Rabbit	Corrosive
2-Butoxyethanol	Rabbit	Severe irritant
Alcohols, C12-16, ethoxylated	Rabbit	Corrosive
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
2-(2-Ethoxyethoxy)ethanol	Human	Not classified
2-Butoxyethanol	Guinea pig	Not classified
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Human and animal	Sensitising

Photosensitisation

Name	Species	Value
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Human and animal	Not sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-(2-Ethoxyethoxy)ethanol	In Vitro	Not mutagenic
2-(2-Ethoxyethoxy)ethanol	In vivo	Not mutagenic
2-Butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	In vivo	Not mutagenic
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
2-Butoxyethanol	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Dermal	Mouse	Not carcinogenic
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2-(2-Ethoxyethoxy)ethanol	Dermal	Not classified for development	Rat	NOAEL 5,500 mg/kg/day	during organogenesis
2-(2-Ethoxyethoxy)ethanol	Ingestion	Not classified for development	Mouse	NOAEL 5,500 mg/kg/day	during organogenesis
2-(2-Ethoxyethoxy)ethanol	Inhalation	Not classified for development	Rat	NOAEL 0.6 mg/l	during organogenesis
2-(2-Ethoxyethoxy)ethanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,200 mg/kg/day	2 generation
2-Butoxyethanol	Dermal	Not classified for development	Rat	NOAEL 1,760 mg/kg/day	during gestation
2-Butoxyethanol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesis
2-Butoxyethanol	Inhalation	Not classified for development	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-(2-Ethoxyethoxy)ethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Sulphuric acid, mono-C10-16-alkyl esters, sodium salts	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
2-Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 902 mg/kg	6 hours
2-Butoxyethanol	Dermal	liver	Not classified	Rabbit	LOAEL 72 mg/kg	not available
2-Butoxyethanol	Dermal	kidney and/or bladder	Not classified	Rabbit	LOAEL 451 mg/kg	6 hours
2-Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-Butoxyethanol	Ingestion	blood	Not classified	Multiple animal species	NOAEL Not available	

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

2-Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Human	NOAEL Not available	poisoning and/or abuse
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-(2-Ethoxyethoxy)ethanol	Dermal	kidney and/or bladder	Not classified	Rabbit	NOAEL 1,000 mg/kg/day	12 weeks
2-(2-Ethoxyethoxy)ethanol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Pig	NOAEL 167 mg/kg/day	90 days
2-(2-Ethoxyethoxy)ethanol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 2,700 mg/kg/day	90 days
2-(2-Ethoxyethoxy)ethanol	Ingestion	endocrine system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
2-(2-Ethoxyethoxy)ethanol	Ingestion	heart hematopoietic system nervous system	Not classified	Mouse	NOAEL 8,100 mg/kg/day	90 days
2-Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 150 mg/kg/day	90 days
2-Butoxyethanol	Inhalation	liver	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
2-Butoxyethanol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	14 weeks
2-Butoxyethanol	Inhalation	blood	Not classified	Rat	LOAEL 0.15 mg/l	6 months
2-Butoxyethanol	Inhalation	endocrine system	Not classified	Dog	LOAEL 1.9 mg/l	8 days
2-Butoxyethanol	Ingestion	blood	Not classified	Rat	LOAEL 69 mg/kg/day	13 weeks
2-Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
----------	-------	----------	------	----------	---------------	-------------

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

Acetic acid, mercapto-, monoammonium salt	5421-46-5		Data not available or insufficient for classification			
2-Butoxyethanol	111-76-2	Eastern oyster	Experimental	96 hours	LC50	89.4 mg/l
2-Butoxyethanol	111-76-2	Green Algae	Experimental	72 hours	EC50	1,840 mg/l
2-Butoxyethanol	111-76-2	Rainbow trout	Experimental	96 hours	LC50	1,474 mg/l
2-Butoxyethanol	111-76-2	Water flea	Experimental	48 hours	EC50	1,550 mg/l
2-Butoxyethanol	111-76-2	Green Algae	Experimental	72 hours	Effect Concentration 10%	679 mg/l
2-Butoxyethanol	111-76-2	Water flea	Experimental	21 days	NOEC	100 mg/l
2-(2-Ethoxyethoxy)ethanol	111-90-0	Green algae	Estimated	96 hours	EC50	>100 mg/l
2-(2-Ethoxyethoxy)ethanol	111-90-0	Channel Catfish	Experimental	96 hours	LC50	6,010 mg/l
2-(2-Ethoxyethoxy)ethanol	111-90-0	Water flea	Experimental	48 hours	LC50	1,982 mg/l
2-(2-Ethoxyethoxy)ethanol	111-90-0	Green algae	Estimated	96 hours	NOEC	100 mg/l
Sodium xylenesulphonate	1300-72-7	Fathead minnow	Experimental	96 hours	LC50	>400 mg/l
Sodium xylenesulphonate	1300-72-7	Green Algae	Experimental	96 hours	EC50	230 mg/l
Sodium xylenesulphonate	1300-72-7	Water flea	Experimental	48 hours	EC50	>400 mg/l
Sodium xylenesulphonate	1300-72-7	Green Algae	Experimental	96 hours	NOEC	31 mg/l
Sulphuric acid, mono-C10-16-alkyl esters, sodium salts	68585-47-7		Data not available or insufficient for classification			
Alcohols, C12-16, ethoxylated	68551-12-2	Diatom	Experimental	72 hours	EC50	1 mg/l
Alcohols, C12-16, ethoxylated	68551-12-2	Fathead minnow	Experimental	96 hours	LC50	0.48 mg/l
Alcohols, C12-16, ethoxylated	68551-12-2	Green algae	Experimental	72 hours	EC50	0.85 mg/l
Alcohols, C12-16, ethoxylated	68551-12-2	Water flea	Experimental	48 hours	EC50	0.302 mg/l
Alcohols, C12-16, ethoxylated	68551-12-2	Diatom	Experimental	72 hours	NOEC	0.32 mg/l
Alcohols, C12-16, ethoxylated	68551-12-2	Green Algae	Experimental	72 hours	NOEC	0.5 mg/l
Alcohols, C12-16, ethoxylated	68551-12-2	Water flea	Experimental	21 days	NOEC	0.083 mg/l
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	55965-84-9	Diatom	Experimental	72 hours	EC50	0.021 mg/l
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	55965-84-9	Water flea	Experimental	48 hours	EC50	0.18 mg/l
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	55965-84-9	Diatom	Experimental	72 hours	NOEC	0.01 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
----------	---------	-----------	----------	------------	-------------	----------

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

Acetic acid, mercapto-, monoammonium salt	5421-46-5	Data not available or insufficient			N/A	
2-Butoxyethanol	111-76-2	Experimental Biodegradation	28 days	CO2 evolution	90.4 % weight	OECD 301B - Modified sturm or CO2
2-(2-Ethoxyethoxy)ethanol	111-90-0	Experimental Biodegradation	16 days	CO2 evolution	100 % weight	OECD 301B - Modified sturm or CO2
Sodium xylenesulphonate	1300-72-7	Experimental Biodegradation	28 days	CO2 evolution	84 % weight	OECD 301B - Modified sturm or CO2
Sulphuric acid, mono-C10-16-alkyl esters, sodium salts	68585-47-7	Experimental Biodegradation	30 days	BOD	>60 % BOD/ThBOD	OECD 301D - Closed bottle test
Alcohols, C12-16, ethoxylated	68551-12-2	Experimental Biodegradation	28 days	BOD	69 % weight	Other methods
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	55965-84-9	Data not available or insufficient			N/A	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Acetic acid, mercapto-, monoammonium salt	5421-46-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Butoxyethanol	111-76-2	Experimental Bioconcentration		Log Kow	0.81	Other methods
2-(2-Ethoxyethoxy)ethanol	111-90-0	Experimental Bioconcentration		Log Kow	-0.54	Other methods
Sodium xylenesulphonate	1300-72-7	Estimated BCF-Carp	42 days	Bioaccumulation factor	=<2.3	OECD 305E - Bioaccumulation flow-through fish test
Sulphuric acid, mono-C10-16-alkyl esters, sodium salts	68585-47-7	Experimental BCF-Carp		Bioaccumulation factor	≤73	Other methods
Alcohols, C12-16, ethoxylated	68551-12-2	Experimental BCF-Carp	72 hours	Bioaccumulation factor	310	
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	55965-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

No information available.

The surfactant(s) contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations

D180101 & D180105, Wheel & Paint Iron DECON (29-46C)

classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

070604* Other organic solvents, washing liquids and mother liquors

SECTION 14: Transportation information

ADR/IATA/IMDG: Not restricted for transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
2-Butoxyethanol	111-76-2	Gr. 3: Not classifiable	International Agency for Research on Cancer

Global inventory status

Contact manufacturer for more information The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH071	Corrosive to the respiratory tract.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. United Kingdom SDSs are available at www.meguiars.co.uk