



## Safety Data Sheet

Copyright,2020, Meguiar's Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	39-4041-8	<b>Version number:</b>	2.00
<b>Revision date:</b>	18/03/2020	<b>Supersedes date:</b>	17/01/2019
<b>Transportation version number:</b>	1.00 (17/01/2019)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Mirror Glaze® Ultra Pro Finishing Polish (Professional) M210 [M21001 M21032]

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Automotive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF  
**Telephone:** +44 (0)870 241 6696  
**E Mail:** info@meguiars.co.uk  
**Website:** www.meguiars.co.uk

#### 1.4. Emergency telephone number

+44 (0)870 241 6696

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
Skin Sensitization, Category 1A - Skin Sens. 1A; H317  
Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373  
Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

**SIGNAL WORD**

WARNING.

**Symbols:**

GHS07 (Exclamation mark) | GHS08 (Health Hazard) |

**Pictograms**



**Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
solvent naphtha (petroleum), medium aliph.	64742-88-7	265-191-7	< 10
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	911-418-6	< 0.002

**HAZARD STATEMENTS:**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system
H412	Harmful to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS**

**General:**

P102 Keep out of reach of children.

**Prevention:**

P260A Do not breathe vapours.  
 P280E Wear protective gloves.

**Response:**

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Information required per Regulation (EU) No 528/2012 on Biocidal Products:**

Contains a biocidal product (preservative): C(M)IT/MIT (3:1).

**Notes on labelling**

H304 is not required on the label due to the product's viscosity

**2.3. Other hazards**

None known.

**SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Non-Hazardous Ingredients	Mixture			60 - 80	Substance not classified as hazardous
Distillates (petroleum), hydro- treated light	64742-47-8	265-149-8		7 - 13	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; Skin Irrit. 2, H315; STOT SE 3, H336
solvent naphtha (petroleum), medium aliph.	64742-88-7	265-191-7		< 10	Asp. Tox. 1, H304; STOT RE 1, H372 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; Skin Irrit. 2, H315
Aluminium oxide	1344-28-1	215-691-6		4 - 9	Substance with a Community level exposure limit in the workplace
White mineral oil (petroleum)	8042-47-5	232-455-8		1 - 5	Asp. Tox. 1, H304
Glycerin	56-81-5	200-289-5		0.5 - 1.5	Substance with a Community level exposure limit in the workplace
Triethanolamine	102-71-6	203-049-8		0.5 - 1.5	Substance not classified as hazardous
PEG Stearate	9004-99-3			0.1 - 1	Aquatic Acute 1, H400,M=1; Aquatic Chronic 3, H412
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	911-418-6		< 0.002	EUH071; Acute Tox. 3, H301; Skin Corr. 1C, H314; Skin Sens. 1A, H317; Aquatic Acute 1, H400,M=100; Aquatic Chronic 1, H410,M=100 - Nota B Acute Tox. 2, H330; Acute Tox. 2, H310

Note: Any entry in the EC# column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.  
Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye contact**

No need for first aid is anticipated.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1 Information on toxicological effects

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

## SECTION 5: Fire-fighting measures

**5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**5.3. Advice for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible.

**6.4. Reference to other sections**

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

**7.2. Conditions for safe storage including any incompatibilities**

No special storage requirements.

**7.3. Specific end use(s)**

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
Aluminium oxide	1344-28-1	UK HSC	TWA(as inhalable dust):10 mg/m <sup>3</sup> ;TWA(as respirable dust):4 mg/m <sup>3</sup>	
Glycerin	56-81-5	UK HSC	TWA(as mist):10 mg/m <sup>3</sup>	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

**Recommended monitoring procedures:**Information on recommended monitoring procedures can be obtained from UK HSC

**8.2. Exposure controls****8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

None required.

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

<b>Material</b>	<b>Thickness (mm)</b>	<b>Breakthrough Time</b>
Polymer laminate	No data available	No data available

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used:Nitrile rubber.

*Applicable Norms/Standards*

Use gloves tested to EN 374

## Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

### Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state

Liquid.

Colour

White

#### Odor

Hydrocarbon

#### Odour threshold

*No data available.*

#### pH

8.2 - 9.2

#### Boiling point/boiling range

100 °C

#### Melting point

*No data available.*

#### Flammability (solid, gas)

Not applicable.

#### Explosive properties

Not classified

#### Oxidising properties

Not classified

#### Flash point

>=93.3 °C [*Test Method: Closed Cup*]

#### Autoignition temperature

*No data available.*

#### Flammable Limits(LEL)

*No data available.*

#### Flammable Limits(UEL)

*No data available.*

#### Vapour pressure

*No data available.*

#### Relative density

1.09 [*Ref Std: WATER=1*]

#### Water solubility

*No data available.*

#### Solubility- non-water

*No data available.*

#### Partition coefficient: n-octanol/water

*No data available.*

#### Evaporation rate

*No data available.*

#### Vapour density

*No data available.*

#### Decomposition temperature

*No data available.*

#### Viscosity

30,000 - 40,000 mPa-s

#### Density

1.09 g/cm<sup>3</sup>

### 9.2. Other information

Average particle size

*No data available.*

Bulk density

*No data available.*

EU Volatile Organic Compounds

*No data available.*

Molecular weight

*No data available.*

Percent volatile

87.6 % weight [*Test Method: Estimated*]

Softening point

*No data available.*

\* The values noted with an asterisk (\*) in the above table are representative values based on testing of raw materials and selected products. Additionally, a material's characteristics may change depending upon the process and conditions of use at a facility, including further changes in particle size, or mixture with other materials. In order to obtain specific data for the material, we recommend the user conduct characterisation testing based on the use factors at the specific facility.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Not determined

### 10.5 Incompatible materials

Not determined

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

#### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Distillates (petroleum), hydro- treated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Distillates (petroleum), hydro- treated light	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Distillates (petroleum), hydro- treated light	Ingestion	Rat	LD50 > 5,000 mg/kg
solvent naphtha (petroleum), medium aliph.	Inhalation-Vapour		LC50 estimated to be 20 - 50 mg/l
solvent naphtha (petroleum), medium aliph.	Dermal	Rabbit	LD50 > 3,000 mg/kg
solvent naphtha (petroleum), medium aliph.	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
White mineral oil (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White mineral oil (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Triethanolamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
Triethanolamine	Ingestion	Rat	LD50 9,000 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Dermal	Rabbit	LD50 87 mg/kg
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Distillates (petroleum), hydro- treated light	Rabbit	Mild irritant
solvent naphtha (petroleum), medium aliph.	Rabbit	Irritant
Aluminium oxide	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	No significant irritation
Triethanolamine	Rabbit	Minimal irritation
Glycerin	Rabbit	No significant irritation
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Rabbit	Corrosive

**Serious Eye Damage/Irritation**

Name	Species	Value
Distillates (petroleum), hydro- treated light	Rabbit	Mild irritant
solvent naphtha (petroleum), medium aliph.	Rabbit	No significant irritation
Aluminium oxide	Rabbit	No significant irritation
White mineral oil (petroleum)	Rabbit	Mild irritant
Triethanolamine	Rabbit	Mild irritant
Glycerin	Rabbit	No significant irritation
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Rabbit	Corrosive

**Skin Sensitisation**



Name	Species	Value
Distillates (petroleum), hydro- treated light	Guinea pig	Not classified
solvent naphtha (petroleum), medium aliph.	Guinea pig	Not classified
White mineral oil (petroleum)	Guinea pig	Not classified
Triethanolamine	Human	Not classified
Glycerin	Guinea pig	Not classified
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Human and animal	Sensitising

### Photosensitisation

Name	Species	Value
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Human and animal	Not sensitising

### Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
Distillates (petroleum), hydro- treated light	In Vitro	Not mutagenic
solvent naphtha (petroleum), medium aliph.	In vivo	Not mutagenic
solvent naphtha (petroleum), medium aliph.	In Vitro	Some positive data exist, but the data are not sufficient for classification
Aluminium oxide	In Vitro	Not mutagenic
White mineral oil (petroleum)	In Vitro	Not mutagenic
Triethanolamine	In Vitro	Not mutagenic
Triethanolamine	In vivo	Not mutagenic
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	In vivo	Not mutagenic
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
Distillates (petroleum), hydro- treated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
solvent naphtha (petroleum), medium aliph.	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
solvent naphtha (petroleum), medium aliph.	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Aluminium oxide	Inhalation	Rat	Not carcinogenic
White mineral oil (petroleum)	Dermal	Mouse	Not carcinogenic
White mineral oil (petroleum)	Inhalation	Multiple animal species	Not carcinogenic
Triethanolamine	Dermal	Multiple animal species	Not carcinogenic
Triethanolamine	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]	Dermal	Mouse	Not carcinogenic

(3:1) reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Ingestion	Rat	Not carcinogenic
--	-----------	-----	------------------

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
solvent naphtha (petroleum), medium aliph.	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
White mineral oil (petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White mineral oil (petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Triethanolamine	Ingestion	Not classified for development	Mouse	NOAEL 1,125 mg/kg/day	during organogenesis
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	2 generation
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), hydro- treated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydro- treated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), hydro- treated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
solvent naphtha (petroleum), medium aliph.	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
solvent naphtha (petroleum), medium aliph.	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for		NOAEL Not available	

			classification			
solvent naphtha (petroleum), medium aliph.	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
solvent naphtha (petroleum), medium aliph.	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
solvent naphtha (petroleum), medium aliph.	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
solvent naphtha (petroleum), medium aliph.	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
solvent naphtha (petroleum), medium aliph.	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
solvent naphtha (petroleum), medium aliph.	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
solvent naphtha (petroleum), medium aliph.	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
White mineral oil (petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White mineral oil (petroleum)	Ingestion	liver   immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Triethanolamine	Dermal	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,000 mg/kg/day	2 years
Triethanolamine	Dermal	liver	Not classified	Mouse	NOAEL 4,000 mg/kg/day	13 weeks
Triethanolamine	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,000 mg/kg/day	2 years
Triethanolamine	Ingestion	liver	Not classified	Guinea pig	NOAEL 1,600 mg/kg/day	24 weeks
Glycerin	Inhalation	respiratory system   heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years

**Aspiration Hazard**

Name	Value
Distillates (petroleum), hydro- treated light	Aspiration hazard

solvent naphtha (petroleum), medium aliph.	Aspiration hazard
White mineral oil (petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Distillates (petroleum), hydro- treated light	64742-47-8	Green Algae	Estimated	72 hours	EC50	1 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Rainbow trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
solvent naphtha (petroleum), medium aliph.	64742-88-7	Green Algae	Estimated	72 hours	Effect Level 50%	8.3 mg/l
solvent naphtha (petroleum), medium aliph.	64742-88-7	Rainbow trout	Estimated	96 hours	Lethal Level 50%	20 mg/l
solvent naphtha (petroleum), medium aliph.	64742-88-7	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
solvent naphtha (petroleum), medium aliph.	64742-88-7	Green Algae	Estimated	72 hours	No obs Effect Level	4 mg/l
solvent naphtha (petroleum), medium aliph.	64742-88-7	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	NOEC	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
White mineral oil (petroleum)	8042-47-5	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l
Glycerin	56-81-5	Rainbow trout	Experimental	96 hours	LC50	54,000 mg/l
Glycerin	56-81-5	Water flea	Experimental	48 hours	LC50	1,955 mg/l

**Mirror Glaze® Ultra Pro Finishing Polish (Professional) M210 [M21001 M21032]**

Triethanolamine	102-71-6	Fathead minnow	Experimental	96 hours	LC50	11,800 mg/l
Triethanolamine	102-71-6	Green algae	Experimental	72 hours	EC50	512 mg/l
Triethanolamine	102-71-6	Water flea	Experimental	48 hours	EC50	609.98 mg/l
Triethanolamine	102-71-6	Green Algae	Experimental	72 hours	Effect Concentration 10%	26 mg/l
Triethanolamine	102-71-6	Water flea	Experimental	21 days	NOEC	16 mg/l
PEG Stearate	9004-99-3	Green algae	Estimated	72 hours	EC50	0.64 mg/l
PEG Stearate	9004-99-3	Water flea	Estimated	48 hours	EC50	0.72 mg/l
PEG Stearate	9004-99-3	Zebra Fish	Estimated	96 hours	LC50	0.65 mg/l
PEG Stearate	9004-99-3	Green algae	Estimated	72 hours	NOEC	0.25 mg/l
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Copepods	Experimental	48 hours	EC50	0.007 mg/l
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Diatom	Experimental	72 hours	EC50	0.0199 mg/l
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Green Algae	Experimental	72 hours	EC50	0.027 mg/l
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Rainbow trout	Experimental	96 hours	LC50	0.19 mg/l
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Sheepshead Minnow	Experimental	96 hours	LC50	0.3 mg/l
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Water flea	Experimental	48 hours	EC50	0.099 mg/l
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Diatom	Experimental	48 hours	NOEC	0.00049 mg/l

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Fathead minnow	Experimental	36 days	No obs Effect Level	0.02 mg/l
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Green Algae	Experimental	72 hours	NOEC	0.004 mg/l
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Water flea	Experimental	21 days	NOEC	0.004 mg/l

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Distillates (petroleum), hydro- treated light	64742-47-8	Data not availbl-insufficient			N/A	
solvent naphtha (petroleum), medium aliph.	64742-88-7	Experimental Biodegradation	28 days	CO2 evolution	55 % weight	OECD 301B - Modified sturm or CO2
Aluminium oxide	1344-28-1	Data not availbl-insufficient			N/A	
White mineral oil (petroleum)	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 % weight	OECD 301B - Modified sturm or CO2
Glycerin	56-81-5	Experimental Biodegradation	14 days	BOD	63 % BOD/ThBOD	OECD 301C - MITI test (I)
Triethanolamine	102-71-6	Experimental Biodegradation	19 days	Dissolv. Organic Carbon Deplet	96 % weight	Other methods
PEG Stearate	9004-99-3	Estimated Biodegradation	28 days	CO2 evolution	85.3 % weight	OECD 301B - Modified sturm or CO2
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Estimated Photolysis		Photolytic half-life (in air)	1.2 days (t 1/2)	Other methods
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Experimental Hydrolysis		Hydrolytic half-life	> 60 days (t 1/2)	Other methods
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Estimated Biodegradation	29 days	CO2 evolution	62 %CO2 evolution/THC O2 evolution (does not pass 10-day window)	OECD 301B - Modified sturm or CO2

## 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Distillates (petroleum), hydro- treated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
solvent naphtha (petroleum), medium aliph.	64742-88-7	Data not available or insufficient for	N/A	N/A	N/A	N/A

**Mirror Glaze® Ultra Pro Finishing Polish (Professional) M210 [M21001 M21032]**

		classification				
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White mineral oil (petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Glycerin	56-81-5	Experimental Bioconcentration		Log Kow	-1.76	Other methods
Triethanolamine	102-71-6	Experimental BCF- Carp	42 days	Bioaccumulation factor	<3.9	Other methods
PEG Stearate	9004-99-3	Estimated Bioconcentration		Bioaccumulation factor	5.5	Estimated: Bioconcentration factor
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	Estimated BCF - Bluegill	28 days	Bioaccumulation factor	54	OECD 305E - Bioaccumulation flow-through fish test

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

**EU waste code (product as sold)**

070104\* Other organic solvents, washing liquids and mother liquors

**SECTION 14: Transportation information**

ADR/IATA/IMDG: Not restricted for transport.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Carcinogenicity**

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Triethanolamine	102-71-6	Gr. 3: Not classifiable	International Agency for Research on Cancer

**15.2. Chemical Safety Assessment**

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

**SECTION 16: Other information**

**List of relevant H statements**

EUH071	Corrosive to the respiratory tract.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision information:**

Section 1: Product name information was modified.  
 CLP: Ingredient table information was modified.  
 Contains statement for sensitizers information was deleted.  
 Label: CLP Classification information was modified.  
 Label: CLP Precautionary - Prevention information was modified.  
 Label: CLP Precautionary - Response information was modified.  
 List of sensitizers information was deleted.  
 Section 3: Composition/ Information of ingredients table information was modified.  
 Section 4: First Aid - notes to physician (REACH/GHS) information was modified.  
 Section 6: Accidental release clean-up information information was modified.  
 Section 08: Skin protection - incidental contact text information was added.  
 Section 08: Skin protection - incidental contact information was added.  
 Section 09: Color information was added.  
 Section 09: Odor information was added.  
 Sections 3 and 9: Odour, colour, grade information information was deleted.  
 Section 11: Acute Toxicity table information was modified.  
 Section 11: Aspiration Hazard Table information was modified.  
 Section 11: Carcinogenicity Table information was modified.  
 Section 11: Germ Cell Mutagenicity Table information was modified.  
 Photosensitisation Table information was modified.



Section 11: Reproductive and/or Developmental Effects text information was deleted.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Section 15: Regulations - Inventories information was deleted.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

Section 16: UK disclaimer information was deleted.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**Meguiar's, Inc. United Kingdom SDSs are available at [www.meguiars.co.uk](http://www.meguiars.co.uk)**