



## Safety Data Sheet

Copyright, 2019, Meguiar's Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	40-3570-5	<b>Version number:</b>	1.01
<b>Revision date:</b>	19/11/2019	<b>Supersedes date:</b>	21/02/2019
<b>Transportation version number:</b>	1.00 (21/02/2019)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

G1923 Ultimate Tyre Shine (31-47A): G192315EU

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Automotive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF  
**Telephone:** +44 (0)870 241 6696  
**E Mail:** info@meguiars.co.uk  
**Website:** www.meguiars.co.uk

#### 1.4. Emergency telephone number

+44 (0)870 241 6696

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Aerosol, Category 1 - Aerosol 1; H222, H229  
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319  
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336  
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

#### 2.2. Label elements

**CLP REGULATION (EC) No 1272/2008****SIGNAL WORD**

DANGER.

**Symbols:**

GHS02 (Flame) | GHS07 (Exclamation mark) | GHS09 (Environment) |

**Pictograms****Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
methyl acetate	79-20-9	201-185-2	20 - 30

**HAZARD STATEMENTS:**

H222	Extremely flammable aerosol.
H229	Pressurised container. may burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS****General:**

P102 Keep out of reach of children.

**Prevention:**

P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.

**Storage:**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Notes on labelling**

H304 is not required on the label because the product is an aerosol.

**2.3. Other hazards**

None known.

**SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Siloxanes and silicones, di-Me	63148-62-9			20 - 30	Substance not classified as hazardous
methyl acetate	79-20-9	201-185-2		20 - 30	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336; EUH066
butane	106-97-8	203-448-7		10 - 20	Flam. Gas 1, H220; Liquified gas, H280 - Nota C,U
acetone	67-64-1	200-662-2		7 - 15	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336; EUH066
Distillates (petroleum), hydro- treated light	64742-47-8	265-149-8		7 - 15	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; Skin Irrit. 2, H315; STOT SE 3, H336
propane	74-98-6	200-827-9		1 - 10	Flam. Gas 1, H220; Liquified gas, H280 - Nota U
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		927-510-4		1 - 10	Aquatic Chronic 2, H411 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336
heptane	142-82-5	205-563-8		1 - 5	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1 - Nota C
toluene	108-88-3	203-625-9		< 0.5	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; Repr. 2, H361d; STOT SE 3, H336; STOT RE 2, H373 Aquatic Chronic 3, H412 Eye Irrit. 2, H319

Note: Any entry in the EC# column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. Get medical attention.

#### Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical

attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1 Information on toxicological effects

**4.3. Indication of any immediate medical attention and special treatment required**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

## SECTION 5: Fire-fighting measures

**5.1. Extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**5.3. Advice for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR-AFFF type foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

**6.4. Reference to other sections**

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not

pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from acids. Store away from oxidising agents.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
butane	106-97-8	UK HSC	TWA:1450 mg/m <sup>3</sup> (600 ppm);STEL:1810 mg/m <sup>3</sup> (750 ppm)	
toluene	108-88-3	UK HSC	TWA: 191 mg/m <sup>3</sup> (50 ppm); STEL: 384 mg/m <sup>3</sup> (100 ppm)	SKIN
heptane	142-82-5	UK HSC	TWA:2085 mg/m <sup>3</sup> (500 ppm)	
acetone	67-64-1	UK HSC	TWA:1210 mg/m <sup>3</sup> (500 ppm);STEL:3620 mg/m <sup>3</sup> (1500 ppm)	
propane	74-98-6	UK HSC	Limit value not established:	asphyxiant
methyl acetate	79-20-9	UK HSC	TWA:616 mg/m <sup>3</sup> (200 ppm);STEL:770 mg/m <sup>3</sup> (250 ppm)	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

**Recommended monitoring procedures:**Information on recommended monitoring procedures can be obtained from UK HSC

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face

protection(s) are recommended:  
 Full face shield.  
 Indirect vented goggles.

*Applicable Norms/Standards*

Use eye/face protection conforming to EN 166

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

*Applicable Norms/Standards*

Use gloves tested to EN 374

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

*Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Appearance**

**Physical state**  
**Colour**

Liquid.  
 Purple

**Odor**

Slight Odor

**Odour threshold**

No data available.

**pH**

No data available.

**Boiling point/boiling range**

No data available.

**Melting point**

No data available.

**Flammability (solid, gas)**

Not applicable.

**Explosive properties**

Not classified

**Oxidising properties**

Not classified

**Flash point**

-17 °C [Test Method:Estimated]

**Autoignition temperature**

No data available.

**Flammable Limits(LEL)**

No data available.

**Flammable Limits(UEL)**

No data available.

**Vapour pressure**

No data available.

**Relative density**

0.873 [Ref Std:WATER=1]

**Water solubility**

No data available.

<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Vapour density</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity</b>	5 mPa-s
<b>Density</b>	0.9 kg/l

**9.2. Other information**

<b>Average particle size</b>	<i>No data available.</i>
<b>Bulk density</b>	<i>No data available.</i>
<b>EU Volatile Organic Compounds</b>	<i>No data available.</i>
<b>Molecular weight</b>	<i>No data available.</i>
<b>Percent volatile</b>	77.2 % weight [ <i>Test Method: Estimated</i> ]
<b>Softening point</b>	<i>No data available.</i>

\* The values noted with an asterisk (\*) in the above table are representative values based on testing of raw materials and selected products. Additionally, a material's characteristics may change depending upon the process and conditions of use at a facility, including further changes in particle size, or mixture with other materials. In order to obtain specific data for the material, we recommend the user conduct characterisation testing based on the use factors at the specific facility.

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.4 Conditions to avoid**

Not determined

**10.5 Incompatible materials**

Strong oxidising agents.

Strong acids.

**10.6 Hazardous decomposition products****Substance**

None known.

**Condition****SECTION 11: Toxicological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**11.1 Information on Toxicological effects**

## Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation

Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

### Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

### Additional Health Effects:

#### Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Cardiac sensitisation: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
methyl acetate	Dermal	Rat	LD50 > 2,000 mg/kg
methyl acetate	Inhalation-Vapour (4 hours)	Rat	LC50 > 49 mg/l
methyl acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Siloxanes and silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Siloxanes and silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
butane	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
acetone	Inhalation-Vapour (4 hours)	Rat	LC50 76 mg/l
acetone	Ingestion	Rat	LD50 5,800 mg/kg
propane	Inhalation-Gas (4	Rat	LC50 > 200,000 ppm



	hours)		
Distillates (petroleum), hydro- treated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Distillates (petroleum), hydro- treated light	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Distillates (petroleum), hydro- treated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Dermal	Rabbit	LD50 > 2,920 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Dermal	Rat	LD50 > 2,000 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation- Vapour (4 hours)	Rat	LC50 > 14.7 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation- Vapour (4 hours)	Rat	LC50 > 23.3 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation- Vapour (4 hours)	Rat	LC50 > 5.61 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Ingestion	Rat	LD50 > 5,840 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Ingestion	Rat	LD50 > 5,000 mg/kg
heptane	Dermal	Rabbit	LD50 3,000 mg/kg
heptane	Inhalation- Vapour (4 hours)	Rat	LC50 103 mg/l
heptane	Ingestion	Rat	LD50 > 15,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation- Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
methyl acetate	Rabbit	No significant irritation
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
butane	Professional judgement	No significant irritation
acetone	Mouse	Minimal irritation
propane	Rabbit	Minimal irritation
Distillates (petroleum), hydro- treated light	Rabbit	Mild irritant
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Rabbit	Irritant
heptane	Human	Mild irritant
toluene	Rabbit	Irritant

#### Serious Eye Damage/Irritation

Name	Species	Value
methyl acetate	Rabbit	Moderate irritant
Siloxanes and silicones, di-Me	Rabbit	No significant irritation
butane	Rabbit	No significant irritation
acetone	Rabbit	Severe irritant
propane	Rabbit	Mild irritant
Distillates (petroleum), hydro- treated light	Rabbit	Mild irritant
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Rabbit	No significant irritation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Rabbit	Mild irritant
heptane	Professional judgement	Moderate irritant
toluene	Rabbit	Moderate irritant

**Skin Sensitisation**

Name	Species	Value
methyl acetate	Human	Not classified
Distillates (petroleum), hydro- treated light	Guinea pig	Not classified
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Guinea pig	Not classified
toluene	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
methyl acetate	In Vitro	Not mutagenic
methyl acetate	In vivo	Not mutagenic
butane	In Vitro	Not mutagenic
acetone	In vivo	Not mutagenic
acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
propane	In Vitro	Not mutagenic
Distillates (petroleum), hydro- treated light	In Vitro	Not mutagenic
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	In Vitro	Not mutagenic
heptane	In Vitro	Not mutagenic
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
acetone	Not specified.	Multiple animal species	Not carcinogenic
Distillates (petroleum), hydro- treated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not specified.	Not classified for development	Rat	NOAEL Not available	2 generation
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure

toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
methyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
methyl acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
methyl acetate	Inhalation	blindness	Not classified		NOAEL Not available	
methyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
butane	Inhalation	cardiac sensitisation	Causes damage to organs	Human	NOAEL Not available	
butane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
butane	Inhalation	heart	Not classified	Dog	NOAEL 5,000 ppm	25 minutes
butane	Inhalation	respiratory irritation	Not classified	Rabbit	NOAEL Not available	
acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
propane	Inhalation	cardiac sensitisation	Causes damage to organs	Human	NOAEL Not available	
propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
Distillates (petroleum), hydro- treated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydro- treated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), hydro- treated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
methyl acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
methyl acetate	Inhalation	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
butane	Inhalation	kidney and/or bladder   blood	Not classified	Rat	NOAEL 4,489 ppm	90 days
acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
acetone	Inhalation	heart   liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
acetone	Ingestion	skin   bone, teeth,	Not classified	Mouse	NOAEL	13 weeks

		nails, and/or hair			11,298 mg/kg/day	
heptane	Inhalation	liver   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 12 mg/l	26 weeks
toluene	Inhalation	auditory system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

### Aspiration Hazard

Name	Value
Distillates (petroleum), hydro- treated light	Aspiration hazard
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Aspiration hazard
heptane	Aspiration hazard
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
methyl acetate	79-20-9	Green algae	Experimental	72 hours	EC50	>120 mg/l
methyl acetate	79-20-9	Water flea	Experimental	48 hours	EC50	1,026.7 mg/l
methyl acetate	79-20-9	Green algae	Experimental	72 hours	NOEC	120 mg/l
Siloxanes and silicones, di-Me	63148-62-9		Data not available or insufficient for classification			
butane	106-97-8		Data not available or insufficient for classification			
acetone	67-64-1	Algae other	Experimental	96 hours	EC50	11,493 mg/l
acetone	67-64-1	Crustacea other	Experimental	24 hours	LC50	2,100 mg/l
acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Green Algae	Estimated	72 hours	EC50	1 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Rainbow trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l
Distillates (petroleum), hydro- treated light	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Fathead minnow	Estimated	96 hours	Lethal Level 50%	8.2 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green Algae	Estimated	72 hours	Effect Level 50%	3.1 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green Algae	Estimated	72 hours	Effect Level 50%	29 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Estimated	48 hours	Effect Level 50%	3 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Estimated	48 hours	Effect Level 50%	4.5 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Rainbow trout	Experimental	96 hours	Lethal Level 50%	>13.4 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4		Data not available or insufficient for classification			
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green Algae	Estimated	72 hours	No obs Effect Level	0.5 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Green Algae	Estimated	72 hours	No obs Effect Level	6.3 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Estimated	21 days	No obs Effect Level	1 mg/l
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Water flea	Estimated	21 days	No obs Effect Level	2.6 mg/l
propane	74-98-6		Data not available or insufficient for			

			classification			
heptane	142-82-5	Water flea	Experimental	48 hours	EC50	1.5 mg/l
heptane	142-82-5	Water flea	Estimated	21 days	NOEC	0.17 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Fish other	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho salmon	Experimental	40 days	NOEC	3.2 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
methyl acetate	79-20-9	Experimental Biodegradation	28 days	BOD	70 % weight	OECD 301D - Closed bottle test
Siloxanes and silicones, di-Me	63148-62-9	Data not available insufficient			N/A	
butane	106-97-8	Experimental Photolysis		Photolytic half-life (in air)	12.3 days (t 1/2)	Other methods
acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	Other methods
acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 % weight	OECD 301D - Closed bottle test
Distillates (petroleum), hydro- treated light	64742-47-8	Data not available insufficient			N/A	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Estimated Biodegradation	28 days	BOD	98 %BOD/CO D	OECD 301F - Manometric respirometry
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Data not available insufficient			N/A	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Estimated Biodegradation	28 days	BOD	77 % BOD/ThBOD	OECD 301F - Manometric respirometry
propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	Other methods
heptane	142-82-5	Experimental Photolysis		Photolytic half-life (in air)	4.24 days (t 1/2)	Other methods
heptane	142-82-5	Experimental Biodegradation	28 days	BOD	101 % BOD/ThBOD	OECD 301C - MITI test (I)
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	Other methods
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 % weight	

## 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
methyl acetate	79-20-9	Experimental Bioconcentration		Log Kow	0.18	Other methods
Siloxanes and silicones, di-Me	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
butane	106-97-8	Experimental Bioconcentration		Log Kow	2.89	Other methods
acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	Other methods
Distillates (petroleum), hydro- treated light	64742-47-8	Data not available or insufficient for	N/A	N/A	N/A	N/A

		classification				
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
propane	74-98-6	Experimental Bioconcentration		Log Kow	2.36	Other methods
heptane	142-82-5	Estimated Bioconcentration		Bioaccumulation factor	105	Estimated: Bioconcentration factor
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	Other methods

#### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

#### 12.6. Other adverse effects

Material	CAS Nbr	Ozone Depletion Potential	Global Warming Potential
acetone	67-64-1	0	

## SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

#### EU waste code (product as sold)

16 05 04\* Gases in pressure containers (including halons) containing dangerous substances

#### EU waste code (product container after use)

15 01 04 Metallic packaging

## SECTION 14: Transportation information

ADR: UN1950; Aerosols; 2.1; (E); 5F.

IATA: UN1950; Aerosols, Flammable; 2.1.

IMDG: UN1950; Aerosols, flammable; 2.1; EMS: FD, SU.



**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Carcinogenicity**

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

**Restrictions on the manufacture, placing on the market and use:**

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
toluene	108-88-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

**15.2. Chemical Safety Assessment**

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

**SECTION 16: Other information****List of relevant H statements**

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container. may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision information:**

CLP: Ingredient table information was modified.

Label: CLP Percent Unknown information was deleted.

Section 3: Composition/ Information of ingredients table information was modified.

Section 7: Conditions safe storage information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 9: Boiling point information information was modified.

Section 09: Color information was added.

Section 09: Odor information was added.  
Sections 3 and 9: Odour, colour, grade information information was deleted.  
Section 11: Acute Toxicity table information was modified.  
Section 11: Aspiration Hazard Table information was modified.  
Section 11: Carcinogenicity Table information was modified.  
Section 11: Germ Cell Mutagenicity Table information was modified.  
Section 11: Reproductive Toxicity Table information was modified.  
Section 11: Serious Eye Damage/Irritation Table information was modified.  
Section 11: Skin Corrosion/Irritation Table information was modified.  
Section 11: Skin Sensitization Table information was modified.  
Section 11: Target Organs - Repeated Table information was modified.  
Section 11: Target Organs - Single Table information was modified.  
Section 12: Component ecotoxicity information information was modified.  
Section 12: Persistence and Degradability information information was modified.  
Section 12: Biocumulative potential information information was modified.  
Section 15: Carcinogenicity information information was modified.  
Section 15: Label remarks and EU Detergent information was deleted.  
Section 15: Regulations - Inventories information was deleted.  
Section 15: Restrictions on manufacture ingredients information was added.  
Section 16: UK disclaimer information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**Meguiar's, Inc. United Kingdom SDSs are available at [www.meguiars.co.uk](http://www.meguiars.co.uk)**